


TC4521BP

TC4521BP 24-STAGE FREQUENCY DIVIDER

TC4521BP is frequency divider consisting of 24 stages of flip-flop. The input section is equipped with an inverter to enable to use either RC oscillator circuit or crystal oscillator circuit and to accept pulse from external clock source.

Each flip-flop is inverted by the falling edge of the output of previous stage flip-flop and this can count up to the maximum of $2^{24} = 16,777,216$.

Since six outputs, 2^{18} , 2^{19} , 2^{20} , 2^{21} , 2^{22} , and 2^{23} are available besides of 2^{24} , adjustment of frequency divided output can be achieved.




P (DIP16-P-300-2.54A)
Weight : 1.00g (Typ.)

MAXIMUM RATINGS


CHARACTERISTIC	SYMBOL	RATING	UNIT
DC Supply Voltage	V_{DD1}	$V_{SS1} - 0.5 \sim V_{SS1} + 20$	V
	V_{DD2}	$V_{SS1} - 0.5 \sim V_{DD1} + 0.5$	
Input Voltage	V_{IN}	$V_{SS1} - 0.5 \sim V_{DD1} + 0.5$	V
Output Voltage	V_{OUT}	$V_{SS1} - 0.5 \sim V_{DD1} + 0.5$	
DC Input Current	I_{IN}	± 10	mA
Power Dissipation	P_D	300	mW
Operating Temperature Range	T_{opr}	$-40 \sim 85$	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	$-65 \sim 150$	$^{\circ}\text{C}$

PIN ASSIGNMENT



(TOP VIEW)

BLOCK DIAGRAM




COUNT CAPACITY

OUTPUT	COUNT CAPACITY
Q18	$2^{18} = 262,144$
Q19	$2^{19} = 524,288$
Q20	$2^{20} = 1,048,576$
Q21	$2^{21} = 2,097,152$
Q22	$2^{22} = 4,194,304$
Q23	$2^{23} = 8,388,608$
Q24	$2^{24} = 16,777,216$


961001EBA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.


LOGIC DIAGRAM



INTERNAL FLIP FLOP LOGIC DIAGRAM



FLIP FLOP TIMING CHART



961001EBA2'

- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

RECOMMENDED OPERATING CONDITIONS ($V_{SS1} = V_{SS2} = 0V$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
DC Supply Voltage	V_{DD1}, V_{DD2}		3	—	18	V
Input Voltage	V_{IN}		0	—	V_{DD1}	V

STATIC ELECTRICAL CHARACTERISTICS ($V_{SS1} = V_{SS2} = 0V$, $V_{DD1} = V_{DD2}$)


CHARACTERISTIC	SYM-BOL	TEST CONDITION	V_{DD} (V)	- 40°C		25°C			85°C		UNIT
				MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.	
High-Level Output Voltage	V_{OH}	$ I_{OUT} < 1\mu A$ $V_{IN} = V_{SS}, V_{DD}$	5	4.95	—	4.95	5.00	—	4.95	—	V
			10	9.95	—	9.95	10.00	—	9.95	—	
			15	14.95	—	14.95	15.00	—	14.95	—	
Low-Level Output Voltage	V_{OL}	$ I_{OUT} < 1\mu A$ $V_{IN} = V_{SS}, V_{DD}$	5	—	0.05	—	0.00	0.05	—	0.05	V
			10	—	0.05	—	0.00	0.05	—	0.05	
			15	—	0.05	—	0.00	0.05	—	0.05	
Output High Current	I_{OH}	$V_{OH} = 4.6V$	5	-0.61	—	-0.51	-1.0	—	-0.42	—	mA
		$V_{OH} = 2.5V$	5	-2.5	—	-2.1	-4.0	—	-1.7	—	
		$V_{OH} = 9.5V$	10	-1.5	—	-1.3	-2.2	—	-1.1	—	
		$V_{OH} = 13.5V$	15	-4.0	—	-3.4	-9.0	—	-2.8	—	
		$V_{IN} = V_{SS}, V_{DD}$									
Output Low Current	I_{OL}	$V_{OL} = 0.4V$	5	0.61	—	0.51	1.2	—	0.42	—	mA
		$V_{OL} = 0.5V$	10	1.5	—	1.3	3.2	—	1.1	—	
		$V_{OL} = 1.5V$	15	4.0	—	3.4	12.0	—	2.8	—	
		$V_{IN} = V_{SS}, V_{DD}$									
Input High Voltage	V_{IH}	$V_{OUT} = 0.5V, 4.5V$	5	3.5	—	3.5	2.75	—	3.5	—	V
		$V_{OUT} = 1.0V, 9.0V$	10	7.0	—	7.0	5.5	—	7.0	—	
		$V_{OUT} = 1.5V, 13.5V$	15	11.0	—	11.0	8.25	—	11.0	—	
		$ I_{OUT} < 1\mu A$									
Input Low Voltage	V_{IL}	$V_{OUT} = 0.5V, 4.5V$	5	—	1.5	—	2.25	1.5	—	1.5	V
		$V_{OUT} = 1.0V, 9.0V$	10	—	3.0	—	4.5	3.0	—	3.0	
		$V_{OUT} = 1.5V, 13.5V$	15	—	4.0	—	6.75	4.0	—	4.0	
		$ I_{OUT} < 1\mu A$									
Input Current	"H" Level	I_{IH}	$V_{IH} = 18V$	18	—	0.1	—	10^{-5}	0.1	—	μA
	"L" Level	I_{IL}	$V_{IL} = 0V$	18	—	-0.1	—	-10^{-5}	-0.1	—	
Quiescent Supply Current	I_{DD}	$V_{IN} = V_{SS}, V_{DD} *$	5	—	5	—	0.005	5	—	150	μA
			10	—	10	—	0.010	10	—	300	
			15	—	20	—	0.015	20	—	600	

* All valid input combinations.

DYNAMIC ELECTRICAL CHARACTERISTICS (Ta = 25°C, V_{SS1} = V_{SS2} = 0V, V_{DD1} = V_{DD2}, C_L = 50pF)


CHARACTERISTIC	SYMBOL	TEST CONDITION	V _{DD} (V)	MIN.	TYP.	MAX.	UNIT
Output Transition Time (Low to High)	t _{TLH}		5 10 15	— — —	70 35 30	200 100 80	ns
Output Transition Time (High to Low)	t _{THL}		5 10 15	— — —	70 35 30	200 100 80	
Propagation Delay Time (IN2 - Q18)	t _{pLH} t _{pHL}		5 10 15	— — —	1.1 0.5 0.3	9.0 3.5 2.7	μs
Propagation Delay Time (IN2 - Q24)	t _{pLH} t _{pHL}		5 10 15	— — —	1.4 0.6 0.4	12 4.5 3.5	
Propagation Delay Time (RESET - Qn)	t _{pHL}		5 10 15	— — —	220 100 70	2600 1000 750	ns
Max. Clock Frequency	f _{CL}		5 10 15	3 6 8	9.5 17.5 23.5	— — —	MHz
Max. Clock Input Rise Time Max. Clock Input Fall Time	t _{rCL} t _{fCL}		5 10 15	No Limit			μs
Min. Clock Pulse Width	t _w		5 10 15	— — —	55 25 16	385 150 120	ns
Min. Pulse Width (RESET)	t _{WH}		5 10 15	— — —	60 26 20	385 150 120	
Input Capacitance	C _{IN}			—	5	7.5	pF

WAVEFORM FOR MEASUREMENT OF DYNAMIC CHARACTERISTICS




APPLICATION CIRCUIT

* When CR oscillation is used as time reference



* When crystal oscillation circuit is used as the time reference




Typical data

X'tal (Hz)	C _i , C _o (pF)	R _o (Ω)
32.768k	23	500k
100k	60	100k
1M	45~50	100
4.194304M	12~15	0

R_f=10MΩ

DIP 16PIN OUTLINE DRAWING (DIP16-P-300-2.54A)

Unit in mm



Weight : 1.00g (Typ.)