

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

'90A, 'LS90 . . . Decade Counters

'92A, 'LS92 . . . Divide By-Twelve Counters

'93A, 'LS93 . . . 4-Bit Binary Counters

| TYPES               | TYPICAL<br>POWER DISSIPATION |
|---------------------|------------------------------|
| '90A                | 145 mW                       |
| '92A, '93A          | 130 mW                       |
| 'LS90, 'LS92, 'LS93 | 45 mW                        |

## description


Each of these monolithic counters contains four master-slave flip-flops and additional gating to provide a divide-by-two counter and a three-stage binary counter for which the count cycle length is divide-by-five for the '90A and 'LS90, divide-by-six for the '92A and 'LS92, and the divide-by-eight for the '93A and 'LS93.

All of these counters have a gated zero reset and the '90A and 'LS90 also have gated set-to-nine inputs for use in BCD nine's complement applications.

To use their maximum count length (decade, divide-by-twelve, or four-bit binary) of these counters, the CKB input is connected to the  $Q_A$  output. The input count pulses are applied to CKA input and the outputs are as described in the appropriate function table. A symmetrical divide-by-ten count can be obtained from the '90A or 'LS90 counters by connecting the  $Q_D$  output to the CKA input and applying the input count to the CKB input which gives a divide-by-ten square wave at output  $Q_A$ .


SN5490A, SN54LS90 . . . J OR W PACKAGE  
SN7490A . . . N PACKAGE  
SN74LS90 . . . D OR N PACKAGE

(TOP VIEW)




SN5492A, SN54LS92 . . . J OR W PACKAGE  
SN7492A . . . N PACKAGE  
SN74LS92 . . . D OR N PACKAGE

(TOP VIEW)



SN5493A, SN54LS93 . . . J OR W PACKAGE  
SN7493 . . . N PACKAGE  
SN74LS93 . . . D OR N PACKAGE


(TOP VIEW)



SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

logic symbols†



†These symbols are in accordance with ANSI/IEEE Std. 91-1984 and IEC Publication 617-12.

SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A - MARCH 1974 - REVISED MARCH 1988

'90A, 'LS90  
 BCD COUNT SEQUENCE  
 (See Note A)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | L              | H              | L              | H              |
| 6     | L              | H              | H              | L              |
| 7     | L              | H              | H              | H              |
| 8     | H              | L              | L              | L              |
| 9     | H              | L              | L              | H              |

'90A, 'LS90  
 BI-QUINARY (5-2)  
 (See Note B)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>A</sub> | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | H              | L              | L              | L              |
| 6     | H              | L              | L              | H              |
| 7     | H              | L              | H              | L              |
| 8     | H              | L              | H              | H              |
| 9     | H              | H              | L              | L              |

'92A, 'LS92  
 COUNT SEQUENCE  
 (See Note C)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | L              | H              | L              | H              |
| 6     | H              | L              | L              | L              |
| 7     | H              | L              | L              | H              |
| 8     | H              | L              | H              | L              |
| 9     | H              | L              | H              | H              |
| 10    | H              | H              | L              | L              |
| 11    | H              | H              | L              | H              |

'90A, 'LS90  
 RESET/COUNT FUNCTION TABLE

| RESET INPUTS       |                    |                    |                    | OUTPUT         |                |                |                |
|--------------------|--------------------|--------------------|--------------------|----------------|----------------|----------------|----------------|
| R <sub>0</sub> (1) | R <sub>0</sub> (2) | R <sub>9</sub> (1) | R <sub>9</sub> (2) | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| H                  | H                  | L                  | X                  | L              | L              | L              | L              |
| H                  | H                  | X                  | L                  | L              | L              | L              | L              |
| X                  | X                  | H                  | H                  | H              | L              | L              | H              |
| X                  | L                  | X                  | L                  | COUNT          |                |                |                |
| L                  | X                  | L                  | X                  | COUNT          |                |                |                |
| L                  | X                  | X                  | L                  | COUNT          |                |                |                |
| X                  | L                  | L                  | X                  | COUNT          |                |                |                |

'93A, 'LS93  
 COUNT SEQUENCE  
 (See Note C)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | L              | H              | L              | H              |
| 6     | L              | H              | H              | L              |
| 7     | L              | H              | H              | H              |
| 8     | H              | L              | L              | L              |
| 9     | H              | L              | L              | H              |
| 10    | H              | L              | H              | L              |
| 11    | H              | L              | H              | H              |
| 12    | H              | H              | L              | L              |
| 13    | H              | H              | L              | H              |
| 14    | H              | H              | H              | L              |
| 15    | H              | H              | H              | H              |

'92A, 'LS92, '93A, 'LS93  
 RESET/COUNT FUNCTION TABLE


| RESET INPUTS       |                    | OUTPUT         |                |                |                |
|--------------------|--------------------|----------------|----------------|----------------|----------------|
| R <sub>0</sub> (1) | R <sub>0</sub> (2) | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| H                  | H                  | L              | L              | L              | L              |
| L                  | X                  | COUNT          |                |                |                |
| X                  | L                  | COUNT          |                |                |                |

- NOTES: A. Output Q<sub>A</sub> is connected to input CKB for BCD count.  
 B. Output Q<sub>D</sub> is connected to input CKA for bi-quinary count.  
 C. Output Q<sub>A</sub> is connected to input CKB.  
 D. H = high level, L = low level, X = irrelevant

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS


SDLS940A – MARCH 1974 – REVISED MARCH 1988

## logic diagrams (positive logic)



The J and K inputs shown without connection are for reference only and are functionally at a high level.  
Pin numbers shown in ( ) are for the 'LS93 and '93A and pin numbers shown in [ ] are for the '54LS93.

## schematics of inputs and outputs




SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

schematics of inputs and outputs (continued)

'LS90, 'LS92, 'LS93



# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

|   |                |
|---|----------------|
| Supply voltage, $V_{CC}$ (see Note 1)                           | 7 V            |
| Input voltage   | 5.5 V          |
| Interemitter voltage (see Note 2)                               | 5.5 V          |
| Operating free-air temperature range: SN5490A, SN5492A, SN5493A | –55°C to 125°C |
| SN7490A, SN7492A, SN7493A                                       | 0°C to 70°C    |
| Storage temperature range                                       | –65°C to 150°C |

NOTES: 1. Voltage values, except interemitter voltage, are with respect to network ground terminal.

2. This is the voltage between two emitters of a multiple-emitter transistor. For these circuits, this rating applies between the two  $R_0$  inputs, and for the '90A circuit, it also applies between the two  $R_0$  inputs.

recommended operating conditions

|   |              | SN5490A, SN5492A<br>SN5493A |     |      | SN7490A, SN7492A<br>SN7493A |     |      | UNIT    |
|---|--------------|-----------------------------|-----|------|-----------------------------|-----|------|---------|
|   |              | MIN                         | NOM | MAX  | MIN                         | NOM | MAX  |         |
| Supply voltage, $V_{CC}$                    |              | 4.5                         | 5   | 5.5  | 4.75                        | 5   | 5.25 | V       |
| High-level output current, $I_{OH}$         |              |                             |     | –800 |                             |     | –800 | $\mu$ A |
| Low-level output current, $I_{OL}$          |              |                             |     | 16   |                             |     | 16   | mA      |
| Count frequency, $f_{count}$ (see Figure 1) | A input      | 0                           |     | 32   | 0                           |     | 32   | MHz     |
|   | B input      | 0                           |     | 16   | 0                           |     | 16   |         |
| Pulse width, $t_W$                          | A input      | 15                          |     |      | 15                          |     |      | ns      |
|   | B input      | 30                          |     |      | 30                          |     |      |         |
|   | Reset inputs | 15                          |     |      | 15                          |     |      |         |
| Reset inactive-state setup time, $t_{SU}$   |              | 25                          |     |      | 25                          |     |      | ns      |
| Operating free-air temperature, $T_A$       |              | –55                         |     | 125  | 0                           |     | 70   | °C      |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER ¶     |  | TEST CONDITIONS†  |   | '90A    |      |     | '92A    |      |     | '93A    |      |     | UNIT |
|-----------------|--|---|---|---------|------|-----|---------|------|-----|---------|------|-----|------|
|                 |  |   |   | MIN     | TYP‡ | MAX | MIN     | TYP‡ | MAX | MIN     | TYP‡ | MAX |      |
| V <sub>IH</sub> | High-level input voltage               |   |   | 2       |      |     | 2       |      |     | 2       |      |     | V    |
| V <sub>IL</sub> | Low-level input voltage                |   |   | 0.8     |      |     | 0.8     |      |     | 0.8     |      |     | V    |
| V <sub>IK</sub> | Input clamp voltage                    | V <sub>CC</sub> = MIN, I <sub>I</sub> = -12 mA  |   | -1.5    |      |     | -1.5    |      |     | -1.5    |      |     | V    |
| V <sub>OH</sub> | High-level output voltage              | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V,<br>V <sub>IL</sub> = 0.8 V, I <sub>OH</sub> = -800 µA |   | 2.4     | 3.4  |     | 2.4     | 3.4  |     | 2.4     | 3.4  |     | V    |
| V <sub>OL</sub> | Low-level output voltage               | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V,<br>V <sub>IL</sub> = 0.8 V, I <sub>OL</sub> = 16 mA¶  |   | 0.2 0.4 |      |     | 0.2 0.4 |      |     | 0.2 0.4 |      |     | V    |
| I <sub>I</sub>  | Input current at maximum input voltage | V <sub>CC</sub> = MAX, V <sub>I</sub> = 5.5 V   |   | 1       |      |     | 1       |      |     | 1       |      |     | mA   |
| I <sub>IH</sub> | High-level input current               | Any reset   | V <sub>CC</sub> = MAX, V <sub>I</sub> = 2.4 V | 40      |      |     | 40      |      |     | 40      |      |     | µA   |
|                 |  | CKA   |   | 80      |      |     | 80      |      |     | 80      |      |     |      |
|                 |  | CKB   |   | 120     |      |     | 120     |      |     | 80      |      |     |      |
| I <sub>IL</sub> | Low-level input current                | Any reset   | V <sub>CC</sub> = MAX, V <sub>I</sub> = 0.4 V | -1.6    |      |     | -1.6    |      |     | -1.6    |      |     | mA   |
|                 |  | CKA   |   | -3.2    |      |     | -3.2    |      |     | -3.2    |      |     |      |
|                 |  | CKB   |   | -4.8    |      |     | -4.8    |      |     | -3.2    |      |     |      |
| I <sub>OS</sub> | Short-circuit output current §         | V <sub>CC</sub> = MAX   | SN54¶   | -20     | -57  | -20 | -57     | -20  | -57 |         |      |     | mA   |
|                 |  |   | SN74¶   | -18     | -57  | -18 | -57     | -18  | -57 |         |      |     |      |
| I <sub>CC</sub> | Supply current                         | V <sub>CC</sub> = MAX, See Note 3   |   | 29 42   |      |     | 26 39   |      |     | 26 39   |      |     | mA   |

<sup>†</sup> For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

<sup>‡</sup> All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

<sup>§</sup> Not more than one output should be shorted at a time.

<sup>¶</sup> QA outputs are tested at  $I_{OL} = 16 \text{ mA}$  plus the limit value for  $I_{IL}$  for the CKB input. This permits driving the CKB input while maintaining full fan-out capability.

NOTE 3:  $I_{CC}$  is measured with all outputs open, both  $R_0$  inputs grounded following momentary connection to 4.5 V, and all other inputs grounded.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265



SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

switching characteristics,  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$

| PARAMETER†       | FROM<br>(INPUT) | TO<br>(OUTPUT)                  | TEST CONDITIONS  | '90A |     |     | '92A |     |     | '93A |     |     | UNIT |
|------------------|-----------------|---------------------------------|--|------|-----|-----|------|-----|-----|------|-----|-----|------|
|                  |                 |                                 |  | MIN  | TYP | MAX | MIN  | TYP | MAX | MIN  | TYP | MAX |      |
| f <sub>max</sub> | CKA             | Q <sub>A</sub>                  | C <sub>L</sub> = 15 pF,<br>R <sub>L</sub> = 400 Ω,<br>See Figure 1 | 32   | 42  |     | 32   | 42  |     | 32   | 42  |     | MHz  |
|                  | CKB             | Q <sub>B</sub>                  |  | 16   |     |     | 16   |     |     | 16   |     |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>A</sub>                  |  | 10   | 16  |     | 10   | 16  |     | 10   | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 12   | 18  |     | 12   | 18  |     | 12   | 18  |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>D</sub>                  |  | 32   | 48  |     | 32   | 48  |     | 46   | 70  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 34   | 50  |     | 34   | 50  |     | 46   | 70  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>B</sub>                  |  | 10   | 16  |     | 10   | 16  |     | 10   | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 14   | 21  |     | 14   | 21  |     | 14   | 21  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>C</sub>                  |  | 21   | 32  |     | 10   | 16  |     | 21   | 32  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 23   | 35  |     | 14   | 21  |     | 23   | 35  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>D</sub>                  |  | 21   | 32  |     | 21   | 32  |     | 34   | 51  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 23   | 35  |     | 23   | 35  |     | 34   | 51  |     |      |
| t <sub>PHL</sub> | Set-to-0        | Any                             |  | 26   | 40  |     | 26   | 40  |     | 26   | 40  |     | ns   |
| t <sub>PLH</sub> | Set-to-9        | Q <sub>A</sub> , Q <sub>D</sub> |  | 20   | 30  |     |      |     |     |      |     |     | ns   |
| t <sub>PHL</sub> |                 | Q <sub>B</sub> , Q <sub>C</sub> |  | 26   | 40  |     |      |     |     |      |     |     |      |

†  $f_{\max}$  = maximum count frequency

$t_{PLH}$  = propagation delay time, low-to-high-level output

$t_{PHL}$  = propagation delay time, high-to-low-level output

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

|  |                |
|--|----------------|
| Supply voltage, $V_{CC}$ (see Note 1)                  | 7 V            |
| Input voltage: R inputs                                | 7 V            |
| A and B inputs   | 5.5 V          |
| Operating free-air temperature range: SN54LS' Circuits | –55°C to 125°C |
| SN74LS' Circuits                                       | 0°C to 70°C    |
| Storage temperature range                              | –65°C to 150°C |

NOTE 1: Voltage values are with respect to network ground terminal.

recommended operating conditions

|   |              | SN54LS90<br>SN54LS92<br>SN54LS93 |     |      | SN74LS90<br>SN74LS92<br>SN74LS93 |     |      | UNIT    |
|---|--------------|----------------------------------|-----|------|----------------------------------|-----|------|---------|
|   |              | MIN                              | NOM | MAX  | MIN                              | NOM | MAX  |         |
| Supply voltage, $V_{CC}$                    |              | 4.5                              | 5   | 5.5  | 4.75                             | 5   | 5.25 | V       |
| High-level output current, $I_{OH}$         |              |                                  |     | –400 |                                  |     | –400 | $\mu$ A |
| Low-level output current, $I_{OL}$          |              |                                  |     | 4    |                                  |     | 8    | mA      |
| Count frequency, $f_{count}$ (see Figure 1) | A input      | 0                                |     | 32   | 0                                |     | 32   | MHz     |
|   | B input      | 0                                |     | 16   | 0                                |     | 16   |         |
| Pulse width, $t_w$                          | A input      | 15                               |     |      | 15                               |     |      | ns      |
|   | B input      | 30                               |     |      | 30                               |     |      |         |
|   | Reset inputs | 30                               |     |      | 30                               |     |      |         |
| Reset inactive-state setup time, $t_{su}$   |              | 25                               |     |      | 25                               |     |      | ns      |
| Operating free-air temperature, $T_A$       |              | –55                              |     | 125  | 0                                |     | 70   | °C      |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER |  | TEST CONDITIONS†   | SN54LS90<br>SN54LS92 |      |      | SN74LS90<br>SN74LS92 |      |      | UNIT    |
|-----------|--|--|----------------------|------|------|----------------------|------|------|---------|
|           |  |  | MIN                  | TYP‡ | MAX  | MIN                  | TYP‡ | MAX  |         |
| $V_{IH}$  | High-level input voltage               |  | 2                    |      |      | 2                    |      |      | V       |
| $V_{IL}$  | Low-level input voltage                |  |                      |      | 0.7  |                      |      | 0.8  | V       |
| $V_{IK}$  | Input clamp voltage                    | $V_{CC} = \text{MIN}, I_I = -18 \text{ mA}$  |                      |      | –1.5 |                      |      | –1.5 | V       |
| $V_{OH}$  | High-level output voltage              | $V_{CC} = \text{MIN}, V_{IH} = 2 \text{ V}, V_{IL} = V_{IL \text{ max}}, I_{OH} = -400 \mu\text{A}$                                  | 2.5                  | 3.4  |      | 2.7                  | 3.4  |      | V       |
| $V_{OL}$  | Low-level output voltage               | $V_{CC} = \text{MIN}, V_{IH} = 2 \text{ V}, V_{IL} = V_{IL \text{ max}}, I_{OL} = 4 \text{ mA}^{\S}$<br>$I_{OL} = 8 \text{ mA}^{\S}$ | 0.25                 | 0.4  |      | 0.25                 | 0.4  |      | V       |
| $I_I$     | Input current at maximum input voltage | Any reset  |                      |      | 0.1  |                      |      | 0.1  | mA      |
|           |  | CKA  |                      |      | 0.2  |                      |      | 0.2  |         |
|           |  | CKB  |                      |      | 0.4  |                      |      | 0.4  |         |
| $I_{IH}$  | High-level input current               | Any reset  |                      |      | 20   |                      |      | 20   | $\mu$ A |
|           |  | CKA  |                      |      | 40   |                      |      | 40   |         |
|           |  | CKB  |                      |      | 80   |                      |      | 80   |         |
| $I_{IL}$  | Low-level input current                | Any reset  |                      |      | –0.4 |                      |      | –0.4 | mA      |
|           |  | CKA  |                      |      | –2.4 |                      |      | –2.4 |         |
|           |  | CKB  |                      |      | –3.2 |                      |      | –3.2 |         |
| $I_{OS}$  | Short-circuit output current $^{\S}$   | $V_{CC} = \text{MAX}$  | –20                  |      | –100 | –20                  |      | –100 | mA      |
| $I_{CC}$  | Supply current                         | $V_{CC} = \text{MAX},$ See Note 3  |                      |      |      |                      |      |      | mA      |
|           |  | 'LS90  | 9                    | 15   |      | 9                    | 15   |      |         |
|           |  | 'LS92  | 9                    | 15   |      | 9                    | 15   |      |         |

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡ All typical values are at  $V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}$ .

$^{\S}$  Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

$^{\S}$   $I_{OL}$  outputs are tested at specified  $I_{OL}$  plus the limit value of  $I_{IL}$  for the CKB input. This permits driving the CKB input while maintaining full fan-out capability.

NOTE 3:  $I_{CC}$  is measured with all outputs open, both R<sub>O</sub> inputs grounded following momentary connection to 4.5 V, and all other inputs grounded.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265



SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER                                     |  |            | TEST CONDITIONS†   | SN54LS93 |      |                         | SN74LS93 |      |      | UNIT |   |
|---|--|------------|--|----------|------|-------------------------|----------|------|------|------|---|
|   |  |            |  | MIN      | TYP‡ | MAX                     | MIN      | TYP‡ | MAX  |      |   |
| V <sub>IH</sub> High-level input voltage      |  |            |  |          |      | 2                       |          | 2    |      | V    |   |
| V <sub>IL</sub> Low-level input voltage       |  |            |  |          |      |                         | 0.7      |      | 0.8  | V    |   |
| V <sub>IK</sub> Input clamp voltage           |  |            | V <sub>CC</sub> = MIN, I <sub>I</sub> = -18 mA   |          |      |                         | -1.5     |      | -1.5 | V    |   |
| V <sub>OH</sub> High-level output voltage     |  |            | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V, V <sub>IL</sub> = V <sub>IL</sub> max, I <sub>OH</sub> = -400 µA |          |      | 2.5                     | 3.4      | 2.7  | 3.4  | V    |   |
| V <sub>OL</sub> Low-level output voltage      |  |            | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V, V <sub>IL</sub> = V <sub>IL</sub> max                            |          |      | I <sub>OL</sub> = 4 mA¶ |          | 0.25 |      | 0.4  | V |
|   |  |            |  |          |      | I <sub>OL</sub> = 8 mA¶ |          | 0.35 |      | 0.5  |   |
| I <sub>I</sub>                                | Input current at maximum input voltage | Any reset  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 7 V  |          |      | 0.1                     |          | 0.1  |      | mA   |   |
|   |  | CKA or CKB | V <sub>CC</sub> = MAX, V <sub>I</sub> = 5.5 V  |          |      | 0.2                     |          | 0.2  |      |      |   |
| I <sub>IH</sub>                               | High-level input current               | Any reset  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 2.7 V  |          |      | 20                      |          | 20   |      | µA   |   |
|   |  | CKA or CKB |  |          |      | 40                      |          | 80   |      |      |   |
| I <sub>IL</sub>                               | Low-level input current                | Any reset  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 0.4 V  |          |      | -0.4                    |          | -0.4 |      | mA   |   |
|   |  | CKA        |  |          |      | -2.4                    |          | -2.4 |      |      |   |
|   |  | CKB        |  |          |      | -1.6                    |          | -1.6 |      |      |   |
| I <sub>OS</sub> Short-circuit output current§ |  |            | V <sub>CC</sub> = MAX  |          |      | -20                     | -100     | -20  | -100 | mA   |   |
| I <sub>CC</sub> Supply current                |  |            | V <sub>CC</sub> = MAX, See Note 3  |          |      | 9                       | 15       | 9    | 15   | mA   |   |

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡ All typical values are at V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C.

§ Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

¶ Q<sub>A</sub> outputs are tested at specified I<sub>OL</sub> plus the limit value for I<sub>IL</sub> for the CKB input. This permits driving the CKB input while maintaining full fan-out capability.

NOTE 3: I<sub>CC</sub> is measured with all outputs open, both R<sub>Q</sub> inputs grounded following momentary connection to 4.5 V, and all other inputs grounded.

switching characteristics, V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C

| PARAMETER#       | FROM<br>(INPUT) | TO<br>(OUTPUT)                  | TEST CONDITIONS  | 'LS90 |     |     | 'LS92 |     |     | 'LS93 |     |     | UNIT |
|------------------|-----------------|---------------------------------|--|-------|-----|-----|-------|-----|-----|-------|-----|-----|------|
|                  |                 |                                 |  | MIN   | TYP | MAX | MIN   | TYP | MAX | MIN   | TYP | MAX |      |
| f <sub>max</sub> | CKA             | Q <sub>A</sub>                  | C <sub>L</sub> = 15 pF,<br>R <sub>L</sub> = 2 kΩ<br>See Figure 1 | 32    | 42  |     | 32    | 42  |     | 32    | 42  |     | MHz  |
|                  | CKB             | Q <sub>B</sub>                  |  | 16    |     |     | 16    |     |     | 16    |     |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>A</sub>                  |  | 10    | 16  |     | 10    | 16  |     | 10    | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 12    | 18  |     | 12    | 18  |     | 12    | 18  |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>D</sub>                  |  | 32    | 48  |     | 32    | 48  |     | 46    | 70  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 34    | 50  |     | 34    | 50  |     | 46    | 70  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>B</sub>                  |  | 10    | 16  |     | 10    | 16  |     | 10    | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 14    | 21  |     | 14    | 21  |     | 14    | 21  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>C</sub>                  |  | 21    | 32  |     | 10    | 16  |     | 21    | 32  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 23    | 35  |     | 14    | 21  |     | 23    | 35  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>D</sub>                  |  | 21    | 32  |     | 21    | 32  |     | 34    | 51  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |  | 23    | 35  |     | 23    | 35  |     | 34    | 51  |     |      |
| t <sub>PHL</sub> | Set-to-0        | Any                             |  | 26    | 40  |     | 26    | 40  |     | 26    | 40  |     | ns   |
| t <sub>PLH</sub> | Set-to-9        | Q <sub>A</sub> , Q <sub>D</sub> |  | 20    | 30  |     |       |     |     |       |     |     | ns   |
| t <sub>PHL</sub> |                 | Q <sub>B</sub> , Q <sub>C</sub> |  | 26    | 40  |     |       |     |     |       |     |     |      |

#f<sub>max</sub> = maximum count frequency

t<sub>PLH</sub> = propagation delay time, low-to-high-level output

t<sub>PHL</sub> = propagation delay time, high-to-low-level output




TEXAS  
INSTRUMENTS

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

## PARAMETER MEASUREMENT INFORMATION



NOTES: A. Input pulses are supplied by a generator having the following characteristics:

for '90A, '92A, '93A,  $t_r \leq 5$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms;  
for 'LS90, 'LS92, 'LS93,  $t_r \leq 15$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms.

B.  $C_L$  includes probe and jig capacitance.

C. All diodes are 1N3064 or equivalent.


D. Each reset input is tested separately with the other reset at 4.5 V.

E. Reference waveforms are shown with dashed lines.

F. For '90A, '92A, and '93A;  $V_{ref} = 1.5$  V. For 'LS90, 'LS92, and 'LS93;  $V_{ref} = 1.3$  V.

FIGURE 1A

## PARAMETER MEASUREMENT INFORMATION



- NOTES: A. Input pulses are supplied by a generator having the following characteristics:  
 for '90A, '92A, '93A,  $t_r \leq 5$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms;  
 for 'LS90, 'LS92, 'LS93,  $t_r \leq 15$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms.
- B.  $C_L$  includes probe and jig capacitance.
- C. All diodes are 1N3064 or equivalent.
- D. Each reset input is tested separately with the other reset at 4.5 V.
- E. Reference waveforms are shown with dashed lines.
- F. For '90A, '92A, and '93A;  $V_{ref} = 1.5$  V. For 'LS90, 'LS92, and 'LS93;  $V_{ref} = 1.3$  V.

FIGURE 1B

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

### Products

|                    |  |
|--------------------|--|
| Amplifiers         | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             |
| Data Converters    | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     |
| DSP                | <a href="http://dsp.ti.com">dsp.ti.com</a>                         |
| Interface          | <a href="http://interface.ti.com">interface.ti.com</a>             |
| Logic              | <a href="http://logic.ti.com">logic.ti.com</a>                     |
| Power Mgmt         | <a href="http://power.ti.com">power.ti.com</a>                     |
| Microcontrollers   | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> |
| Low Power Wireless | <a href="http://www.ti.com/lpw">www.ti.com/lpw</a>                 |

### Applications

|                    |  |
|--------------------|--|
| Audio              | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Automotive         | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| Broadband          | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Digital Control    | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Military           | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Optical Networking | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Security           | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
| Telephony          | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
| Video & Imaging    | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
| Wireless           | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2007, Texas Instruments Incorporated



**PACKAGING INFORMATION**

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| 7603201CA        | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| 7603201DA        | ACTIVE                | CFP          | W               | 14   | 1           | TBD                     | A42              | N / A for Pkg Type           |
| 7700101CA        | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| 7700101DA        | ACTIVE                | CFP          | W               | 14   | 1           | TBD                     | A42              | N / A for Pkg Type           |
| JM38510/31501BCA | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| JM38510/31501BDA | ACTIVE                | CFP          | W               | 14   | 1           | TBD                     | A42              | N / A for Pkg Type           |
| JM38510/31502BCA | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| JM38510/31502BDA | ACTIVE                | CFP          | W               | 14   | 1           | TBD                     | A42              | N / A for Pkg Type           |
| SN5490AJ         | OBSOLETE              | CDIP         | J               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN5492AJ         | OBSOLETE              | CDIP         | J               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN54LS90J        | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| SN54LS93J        | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| SN7490AN         | OBSOLETE              | PDIP         | N               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN7492AN         | OBSOLETE              | PDIP         | N               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN7493AN         | OBSOLETE              | PDIP         | N               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN74LS90D        | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS90DE4      | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS90DG4      | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS90DR       | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS90DRE4     | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS90DRG4     | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS90N        | ACTIVE                | PDIP         | N               | 14   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | N / A for Pkg Type           |
| SN74LS90NE4      | ACTIVE                | PDIP         | N               | 14   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | N / A for Pkg Type           |
| SN74LS92D        | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92DE4      | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92DG4      | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92DR       | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92DRE4     | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92DRG4     | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92N        | ACTIVE                | PDIP         | N               | 14   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | N / A for Pkg Type           |
| SN74LS92N3       | OBSOLETE              | PDIP         | N               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN74LS92NE4      | ACTIVE                | PDIP         | N               | 14   | 25          | Pb-Free                 | CU NIPDAU        | N / A for Pkg Type           |



| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| (RoHS)           |                       |              |                 |      |             |                         |                  |                              |
| SN74LS92NSR      | ACTIVE                | SO           | NS              | 14   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92NSRE4    | ACTIVE                | SO           | NS              | 14   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS92NSRG4    | ACTIVE                | SO           | NS              | 14   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93D        | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93DE4      | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93DG4      | ACTIVE                | SOIC         | D               | 14   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93DR       | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93DRE4     | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93DRG4     | ACTIVE                | SOIC         | D               | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93N        | ACTIVE                | PDIP         | N               | 14   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | N / A for Pkg Type           |
| SN74LS93N3       | OBSOLETE              | PDIP         | N               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SN74LS93NE4      | ACTIVE                | PDIP         | N               | 14   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | N / A for Pkg Type           |
| SN74LS93NSR      | ACTIVE                | SO           | NS              | 14   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93NSRE4    | ACTIVE                | SO           | NS              | 14   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74LS93NSRG4    | ACTIVE                | SO           | NS              | 14   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SNJ5490AJ        | OBSOLETE              | CDIP         | J               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SNJ5490AW        | OBSOLETE              | CFP          | W               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SNJ5492AJ        | OBSOLETE              | CDIP         | J               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SNJ5492AW        | OBSOLETE              | CFP          | W               | 14   |             | TBD                     | Call TI          | Call TI                      |
| SNJ54LS90J       | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| SNJ54LS90W       | ACTIVE                | CFP          | W               | 14   | 1           | TBD                     | A42              | N / A for Pkg Type           |
| SNJ54LS93J       | ACTIVE                | CDIP         | J               | 14   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| SNJ54LS93W       | ACTIVE                | CFP          | W               | 14   | 1           | TBD                     | A42              | N / A for Pkg Type           |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered

at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.


**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


**TAPE AND REEL INFORMATION**



\*All dimensions are nominal

| Device      | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LS90DR  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LS92DR  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LS92NSR | SO           | NS              | 14   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| SN74LS93DR  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LS93NSR | SO           | NS              | 14   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal


| Device      | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LS90DR  | SOIC         | D               | 14   | 2500 | 346.0       | 346.0      | 33.0        |
| SN74LS92DR  | SOIC         | D               | 14   | 2500 | 346.0       | 346.0      | 33.0        |
| SN74LS92NSR | SO           | NS              | 14   | 2000 | 346.0       | 346.0      | 33.0        |
| SN74LS93DR  | SOIC         | D               | 14   | 2500 | 346.0       | 346.0      | 33.0        |
| SN74LS93NSR | SO           | NS              | 14   | 2000 | 346.0       | 346.0      | 33.0        |

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



| DIM \ PINS ** | 14    | 16    | 20    | 24    |
|---------------|-------|-------|-------|-------|
| A MAX         | 10,50 | 10,50 | 12,90 | 15,30 |
| A MIN         | 9,90  | 9,90  | 12,30 | 14,70 |

4040062/C 03/03


- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.




J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |




4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

## D (R-PDSO-G14)

## PLASTIC SMALL-OUTLINE PACKAGE




4040047-3/H 11/2006

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 (0,15) per end.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed .017 (0,43) per side.
  - E. Reference JEDEC MS-012 variation AB.

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK




- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a ceramic lid using glass frit.
  - Index point is provided on cap for terminal identification only.
  - Falls within MIL STD 1835 GDFP1-F14 and JEDEC MO-092AB


N (R-PDIP-T\*\*)

16 PINS SHOWN

PLASTIC DUAL-IN-LINE PACKAGE



| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

### Products

|                             |  |
|-----------------------------|--|
| Amplifiers                  | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             |
| Data Converters             | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     |
| DSP                         | <a href="http://dsp.ti.com">dsp.ti.com</a>                         |
| Clocks and Timers           | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>           |
| Interface                   | <a href="http://interface.ti.com">interface.ti.com</a>             |
| Logic                       | <a href="http://logic.ti.com">logic.ti.com</a>                     |
| Power Mgmt                  | <a href="http://power.ti.com">power.ti.com</a>                     |
| Microcontrollers            | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> |
| RFID                        | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>               |
| RF/IF and ZigBee® Solutions | <a href="http://www.ti.com/lprf">www.ti.com/lprf</a>               |

### Applications

|                    |  |
|--------------------|--|
| Audio              | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Automotive         | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| Broadband          | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Digital Control    | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Medical            | <a href="http://www.ti.com/medical">www.ti.com/medical</a>               |
| Military           | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Optical Networking | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Security           | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
| Telephony          | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
| Video & Imaging    | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
| Wireless           | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2008, Texas Instruments Incorporated