

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

1

2

4

3

5

Ø14.53 MAX  
[.572]

33.53 MAX  
[1.320]

FIGURE 1

FIGURE 2

RECOMMENDED STRIP LENGTH

1

2

3

4

5

6

7

8

9

10

CABLE USED WITHOUT SPACER

CABLE USED WITH SPACER

SEE I.S. 9021

PARTS PACKAGED UNASSEMBLED

USE AMP HAND TOOL: 220190-1

SPECIAL PACKAGING: INDIVIDUALLY PACKAGED IN PRE-PRINTED BAG WITH SPECIAL GRAPHICS

CONNECTOR INDIVIDUALLY PACKAGED

BULK PACKAGE

RG-188/U, 316/U TYPE DOUBLE BRAID AND JIS CABLES 1.5D-2V, 1.5D-XV & 1.5D-XVS

SPECIAL PACKAGING: BULK PACKAGE 25 PIECES

|                           |                    |                               |         |         |              |              |              |               |                     |                     |             |            |          |            |
|---------------------------|--------------------|-------------------------------|---------|---------|--------------|--------------|--------------|---------------|---------------------|---------------------|-------------|------------|----------|------------|
| OBSOLETE                  | 6                  | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | 227423-1            | 9-221132-1  | 222246-6   | 413636-2 | 9-221128-9 |
| OBSOLETE                  | 6                  | BELDEN 9907, 89907 & RG-141/U | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 1-222246-6 | 413636-1 | 9-221128-8 |
| OBSOLETE                  | 6                  | RG-180/U, 195/U               | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | -                   | -                   | 9-413658-1  | 1-222246-3 | 413636-3 | 9-221128-7 |
|                           | 6                  | RG-179/U, 187/U               | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | 227194-1            | -                   | 9-413658-0  | 1-222246-3 | 413636-3 | 9-221128-6 |
|                           | 6                  | RG-174/U, 188/U, 316/U        | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | 227194-1            | -                   | 9-413658-0  | 1-222246-0 | 413636-3 | 9-221128-5 |
| OBSOLETE                  | 6                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-5   | 413636-1 | 9-221128-4 |
| OBSOLETE                  | 7                  | BELDEN 8281                   | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-2   | 413636-4 | 9-221128-3 |
| OBSOLETE                  | 10                 | RG-62/U, 62A/U, 62B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 2         | -                   | -                   | 9-221132-2  | 222246-2   | 413636-4 | 9-221128-3 |
| OBSOLETE                  | 10                 | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | 227423-1            | 9-221132-1  | 222246-4   | 413636-2 | 9-221128-2 |
| OBSOLETE                  | 6                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-2   | 413636-1 | 9-221128-1 |
| OBSOLETE                  | 6                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-2   | 413636-1 | 9-221128-0 |
| OBSOLETE                  | 6                  | BELDEN 1167A                  | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | -                   | -                   | 9-413658-1  | 1-222246-0 | 413636-3 | 3-221128-4 |
| OBSOLETE                  | 10                 | JIS CABLE 3D-2V               | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | 227194-1            | -                   | 9-413658-2  | 1-222246-0 | 413636-3 | 3-221128-2 |
| SUPERSEDED BY 2-221128-5  | 10                 | RG-180/U, 195/U               | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 8-221132-9  | 1-222246-6 | 413636-6 | 3-221128-1 |
| OBSOLETE                  | -                  | BELDEN 9907, 89907 & RG-141/U | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | -                   | -                   | 9-413658-1  | 1-222246-3 | 413636-3 | 3-221128-0 |
|                           | 6                  | RG-180/U, 195/U               | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | 227194-1            | -                   | 9-413658-2  | 1-222246-0 | 413636-3 | 2-221128-9 |
|                           | 6                  | RG-179/U, 187/U               | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 1-222246-6 | 413636-1 | 2-221128-7 |
|                           | 6                  | RG-174/U, 188/U, 316/U        | 4.52    | [.178]  | 1.73         | [.068]       | 58465-3      | FIG 1         | -                   | -                   | 9-413658-1  | 1-222246-3 | 413636-3 | 2-221128-5 |
| SUPERSEDED BY 2-5221128-1 | 6                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | 227194-1            | -                   | 9-413658-0  | 1-222246-0 | 413636-3 | 2-221128-1 |
| OBSOLETE                  | 6                  | BELDEN 8281                   | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-5   | 413636-1 | 2-221128-0 |
| SUPERSEDED BY 1-221128-2  | 6                  | RG-59/U, 59A/U, 59B/U         | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-5   | 413636-4 | 1-221128-9 |
|                           | 6                  | BELDEN 9266                   | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | 227423-1            | 9-221132-1  | 222246-6   | 413636-2 | 1-221128-8 |
|                           | 6                  | BELDEN 9209                   | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-2   | 413636-2 | 1-221128-7 |
| SUPERSEDED BY 1-221128-2  | 7                  | BELDEN 8281                   | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-6   | 413636-5 | 1-221128-6 |
|                           | 7                  | RG-62/U, 62A/U, 62B/U         | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-5   | 413636-4 | 1-221128-5 |
|                           | 7                  | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 2         | -                   | 227423-1            | 9-221132-1  | 222246-6   | 413636-2 | 1-221128-4 |
|                           | 7                  | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-6   | 413636-2 | 1-221128-4 |
|                           | 7                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-5   | 413636-1 | 1-221128-3 |
|                           | 7                  | BELDEN 8281                   | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-2   | 413636-4 | 1-221128-2 |
|                           | 10                 | RG-62/U, 62A/U, 62B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 2         | -                   | 227423-1            | 9-221132-1  | 222246-4   | 413636-2 | 1-221128-1 |
|                           | 10                 | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-4   | 413636-2 | 1-221128-1 |
|                           | 6                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-2   | 413636-1 | 1-221128-0 |
| OBSOLETE                  | -                  | BELDEN 8281                   | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-7   | 413636-4 | 221128-9   |
| OBSOLETE                  | 10                 | RG-62/U, 62A/U, 62B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 2         | -                   | 227423-1            | 9-221132-1  | 222246-8   | 413636-2 | 221128-8   |
| OBSOLETE                  | 10                 | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-8   | 413636-2 | 221128-8   |
| OBSOLETE                  | -                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-7   | 413636-1 | 221128-7   |
| SUPERSEDED BY 221128-3    | -                  | BELDEN 8281                   | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-5   | 413636-4 | 221128-6   |
|                           | 10                 | RG-62/U, 62A/U, 62B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 2         | -                   | 227423-1            | 9-221132-1  | 222246-6   | 413636-2 | 221128-5   |
| SUPERSEDED BY 221128-2    | 10                 | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-5   | 413636-1 | 221128-4   |
| SUPERSEDED BY 221128-1    | -                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-2   | 413636-4 | 221128-3   |
| OBSOLETE                  | -                  | BELDEN 8281                   | 8.23    | [.324]  | 1.73         | [.068]       | 58465-2      | FIG 1         | -                   | -                   | 9-221132-2  | 222246-2   | 413636-4 | 221128-3   |
|                           | 10                 | RG-62/U, 62A/U, 62B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 2         | -                   | 227423-1            | 9-221132-1  | 222246-4   | 413636-2 | 221128-2   |
|                           | 10                 | RG-59/U, 59A/U, 59B/U         | 6.48    | [.255]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-1  | 222246-4   | 413636-2 | 221128-2   |
|                           | -                  | RG-58/U, 58A/U, 58B/U, 58C/U  | 5.41    | [.213]  | 1.73         | [.068]       | 58465-1      | FIG 1         | -                   | -                   | 9-221132-0  | 222246-2   | 413636-1 | 221128-1   |
| REMARKS                   | FOR USE WITH CABLE | FERRULE                       | CONTACT | DIE SET | STRIP LENGTH | TUBING QTY=1 | SPACER QTY=1 | FERRULE QTY=1 | CONTACT, PLUG QTY=1 | PLUG ASSEMBLY QTY=1 | PART NUMBER |            |          |            |
|                           |                    | HEX CRIMP HEIGHTS             |         | 5       | 5            |              |              |               |                     |                     |             |            |          |            |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± 0.41 [016] 3 PLC ± - 4 PLC ± - ANGLES ± - FINISH -

DWN M. E. COWHER 11-18-92

CHK M. PHILLIPS 1-29-93

APVD M. PHILLIPS 1-29-93

NAME

PRODUCT SPEC

APPLICATION SPEC

SIZE CASE CODE DRAWING NO RESTRICTED TO

WEIGHT 0.000000

A100779C=221128

CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV AD3

TE Connectivity

PLUG, COMMERCIAL BNC

4805 (1/15)