



Connectors > Power Connectors > Circular Power > Circular Power Connectors > CPC SERIES 3



Product Type: **Housing**  
Operating Voltage: **600 VDC**  
Connector System: **Wire-to-Wire**  
Number of Positions: **7**  
Sealable: **No**

[All CPC SERIES 3 \(16\)](#)

Features

Product Type Features

Product Type	Housing
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Housing Type	Plug
Contact Type	Pin
Shell Type	All Plastic

Configuration Features

Number of Positions	7
Number of Power Positions	7
Number of Signal Positions	0

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Reverse Gender	Reverse
Contact Current Rating (Max)	32 A
Contact Protection	With

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Panel Mount Feature Type	Flange
Screw & Hole Thread Size	1-3/8 - 18 UNEF-2A
Connector Mounting Type	Cable Mount (Free-Hanging)
Mating Alignment	With
Mating Retention	With
Panel Mount Feature	With

Housing Features

Housing Color	Black
Housing Material	PA 6.6 GF
Shell Size	23
UL Flammability Rating	UL 94V-0

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Shielded	No
Fluid Resistance	None

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Method	Standard
------------------	----------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUL 2019 (201) Candidate List Declared Against: JAN 2019 (197) Does not contain REACH SVHC
EU REACH Regulation (EC) No. 1907/2006	