

a vital part of your world

Find Answers:

Sunday, 20 November, 2005

CATALOG

Cross Reference

Competitive Products Military Spec P/Ns Tyco Brand P/Ns

- Part Number Search
- Document Search
- Product Type Search
- Product Family Search
- Alphabetical Search
- * RoHS/ELV Compliance & Alternates
- CAD Model Search
- Brand Search
- Tool Search
- Multiple Part Comparison
- Lead Free Solutions
- Help/Glossary

Home

e-bulletin newsletter SUBSCRIBE NOW! click here

Subminiature and Microminiature D Connectors → Standard Cable Connectors

AMP

747306-2



Active

(Corporate P/N: 747306-2)

Not ELV or RoHS Compliant

Search for Compliant (RoHS/ELV) **Alternates**

CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information			
General Information	eCommerce	Related Part Information	
 General Info Sales Info Assembly Subcontractors 	➤ Pricing & Availability	→ Tooling	

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo

Panel Mount Cutout Dimensions

Searchable Features:		
Brand:	AMP	
RoHS/ELV Compliance:	Not ELV/RoHS compliant	
Lead Free Solder Processes:	Not relevant for lead free process	
Product Type:	Connector	
Product Series:	HDF-20 (Ribbon Cable)	
Number of Positions:	25	
Gender:	Plug	
Contacts:	With	
Wire/Cable Type:	Ribbon Cable	

Other Properties:			
Profile:	Low		
Ribbon Cable Centerline Spacing (mm [in]):	1.27 [0.050]		
Contact Material:	Phosphor Bronze		
Color:	Black		
Housing Material:	Thermoplastic		
Housing Material Flammability Rating:	UL 94V-0		
Shell Material:	Steel		
Shell Plating:	Tin		
Strain Relief Part Number:	747275-2		
Cover Material:	Thermoplastic		

Wire Termination Type:	Insulation Displacement Crimp (IDC)
Wire Range (mm² [AWG]):	0.08 - 0.15 [28-26]
Mating Connector Lock:	With
Mating Connector Lock Type:	Mounting Holes
Shell Size:	3
Shell Type:	Full Metal Shell
Contact Mating Area Plating:	Gold (30)
Contact Termination Area Plating:	Tin Lead over Nickel
Contact Size:	20
Grounding Indents:	With
Grade:	Standard

Comment:

All plug assemblies are supplied with housing and cover preassembled Mass Termination

Copyright and Privacy Statement Visit Tyco International Ltd.

[Products | Catalog | Brands | Industries | Commerce | Supplier | Contact Us | About | Home]