

Technical Data Sheet

Metallized Polypropylene Film Capacitors - MKP

Powder Dipped


Product Code:

B32611-L7472-K008

Customer Ref

Construction

- Dielectric: polypropylene
- Wound capacitor technology
- Epoxy resin coating (UL 94 V-0)
- · RoHS compatible



Terminals

Radial, straight version, tinned

Marking

- EPCOS logo
- Manufacturing date (year / month coded)
- Rated capacitance and tolerance (coded)
- Rated dc voltage

Delivery Mode

1000 pieces (bulk)

Rated capacitance C:

Dimensions

Electrical Characteristics

Capacitance tolerance: ± 10 % Rated DC voltage Urdc: 1250 Vdc Rated AC voltage Urac: 500 Vac Rated Peak-to-peak voltage Urpp: 1250 Vpp Climatic category according to IEC 68-1 55/100/56 Lower category temperature T_{min}: -55 ºC Upper category temperature T_{max}: +100 ºC Pulse handling capability (dV/dt): ≤ 1000 V/us $\leq 2500000 \text{ V}^2/\mu\text{s}$ Pulse characteristic K₀ $\leq 0.8 \times 10^{-3}$ Loss factor (tang δ) @ 20°C, 10 kHz:

4.7 nF

Loss factor (tang δ) @ 20°C, 10 kHz: Insulation Resistance R_{is} at 20°C, 100V

rel. Humidity \leq 65% \geq 100 G Ω Voltage derating at high temperature (> 85 $^{\circ}$ C) 1.25%/°C

Issued by: Edmundo Werner Neto, FK EDC

Ed.: 1

Date: June, 22nd/06

Notes: Please take all additional data not mentioned above from our data book

English Version:

[©] EPCOS AG 2005. All Rights Reserved. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this data sheet describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.