



Ceramic Resonator&Filter&Trap Series

High Frequency Series

No.	Pictures	Product P/N.
1		ZTA□□□M□series
2		ZTT□□□M□
3		LT□□□MB LTH□□□MCB
4		XT4.5MB XT5.5~6.5MB XT3.58MJ XT4.43MJ

5		<u>LT10. 7MA20</u> <u>LT10. 7MA5</u> <u>LT10. 7MS2</u> <u>LT10. 7MS3</u> <u>LT10. 7MJ</u> <u>LT10. 7MH</u>
6		<u>JT10. 7MG</u>
7		<u>ZTAC□□□MG</u> <u>ZTTC□□□MG</u>

型号 ModelI	频率范围 Frequency Iange (MHz)	频率精度 Frequency Accuracy (25℃)	温度稳定性 Temperature Stability (-20~+80℃)	工作温度 Operating Temperature	老化性（10 年） Age (Ten Years)
ZTA□□□MG	2.00 ~ 6.05	±0.5%	±0.3%	-20 ~ +80℃	±0.3%
ZTA□□□MT	5.00 ~ 12.0		±0.5%		±0.5%
ZTA□□□MX	12.1 ~ 40.0		±0.3%		±0.3%

型号 ModelI	频率范围 Frequency Iange (MHz)	频率精度 Frequency Accuracy (25℃)	温度稳定性 Temperature Stability (-20~+80℃)	工作温度 Operating Temperature	老化性（10 年） Age (Ten Years)
ZTT□□□MG	2.00 ~ 6.00	±0.5%	±0.3%	-20 ~ +80℃	±0.3%
ZTT□□□MT	5.00 ~ 12.0		±0.5%		±0.5%
ZTT□□□MX	12.1 ~ 40.0		±0.3%		±0.3%

型号 Model	3 分贝带宽 3dB band Width (KHz)min	20 分贝带宽 20dB Band Width (KHz)max	插入衰减 Insertion Loss (dB)max	阻带防卫度 Stop Band Att (dB)min	输入/输出阻抗 In/Output Impedance (Ω)
LT4. 5MB	±60	530	6	20 (4. 5 MHz 内)*	1K
LT5. 5MB	±75	550	6	25 (5. 5±1MHz 内)	600
LT6. 0MB	±80	600	6	25 (6. 0±1MHz 内)	470
LT6. 5MB	±80	630	6	25 (6. 5±1MHz 内)	470
LTH4. 5MCB	±60	600	6	30 (0~4. 5±1MHz 内)	1K
LTH5. 5MCB	±60	600	6	30 (0~5. 5±1MHz 内)	600
LTH6. 0MCB	±60	600	6	30 (0~6. 0±1MHz 内)	470
LTH6. 5MCB	±70	650	6	30 (0~6. 5±1MHz 内)	470

型号 Model	标称频率点的衰减量 Attenuation at Reference Frequency (dB)min	30 分贝衰减带宽 (KHz)min
XT4. 5MB	35	50
XT5. 5~6. 5MB		70
XT3. 58MJ	20	20
XT4. 43MJ		40

型号 Model	3 分贝带宽 3dB band Width (KHz)	20 分贝带宽 20dB Band Width (KHz) max	插入损耗 Insertion Loss (dB) max	阻带防卫度 Stop Band Att (dB) min
LT10. 7MA20	330±50	680	6	30
LT10. 7MA5	280±50	650	6	30
LT10. 7MS2	230±50	600	6	40
LT10. 7MS3	180±50	520	7	40
LT10. 7MJ	150±50	400	10	35
LT10. 7MH	110±30	350	10	30

型号 Model	伴音解调输出 Recovered Audio Output Voltage (MV) min	解调失真系数 Distortion Faction (%) max	伴音解调 3dB 带宽 Recovered Audio 3dB Band Width (KHz) min	检波方式 Detection Mode	应用电路 Applied IC
JT10. 7MG	70	1	450	正交检波 Quadrature	CX20029, BA4234AL TA7640AP
	200		300	微分峰值检波 Differential Peak	TA7303P, TA7411AP

型号 Model I	频率范围 Frequency Range (MHz)	频率精度 Frequency Accuracy (25℃)	温度稳定性 Temperature Stability (-20~+80℃)	工作温度 Operating Temperature	老化性 (10 年) Age (Ten Years)
ZTAC□□ □MG	2.00 ~ 6.05	±0.5%	±0.5%	-20 ~ +80 ℃	±0.3%
ZTTC□□ □MG	2.00 ~ 6.00				±0.3%