

UL Online Certifications Directory

XGPU2.E138827
Thermistor Type Devices - Component

Page Bottom

Thermistor Type Devices - Component

See General Information for Thermistor Type Devices - Component

HINKING ELECTRONIC INDUSTRIAL CO LTD

1 LANE 373 MINTSU 1ST RD

AN-MING DIST

AOHSIUNG, 80759 TAIWAN

E138827

Surge Limiting NTC:

Model No.	Voltage (V)	Current (A)		Max Load Capacitance (uF)	CA
		I _{max}	I _{ss}		
Type SCK f/b -037	240	8.4	7.0	470	1(200),4,#
-052		2.4	2.0	100	1(150),4,#
-053		3.6	3.0	100	1(170),4,#
-054		4.8	4.0	220	1(170),4,#
-055		6.0	5.0	150	1(200),4,#
-056		7.2	6.0	470	1(200),4,#
-057		8.4	7.0	470	1(200),4,#
-075		6.0	5.0	470	1(200),4,#
-082		2.4	2.0	100	1(170),4,#
-083		3.6	3.0	220	1(170),4,#
-084		4.8	4.0	330	1(200),4,#
-101		1.2	1.0	100	1(150),4,#
-102		2.4	2.0	100	1(170),4,#
-103		3.6	3.0	330	1(170),4,#
-104		4.8	4.0	330	1(200),4,#
-105		6.0	5.0	680	1(200),4,#
-122		2	2	470	1(131),4,#
-164		4.8	4.0	680	1(200),4,#
-184		4.8	4.0	680	1(196),4,#
-202		2.4	2.0	330	1(170),4,#
-203		3.6	3.0	470	1(200),4,#
-204		4.8	4.0	680	1(200),4,#
-253		3.6	3.0	680	1(200),4,#
-403		3.6	3.0	680	1(200),4,#
-473		3.6	3.0	680	1(200),4,#
-501X		1.8	1.5	330	1(170),4,#

-1R38	9.6	8.0	470	1(200),4,#
-2R55A	6.0	5.0	220	1(170),4,#
-2R56	7.2	6.0	100	1(200),4,#
-2R58	9.6	8.0	470	1(200),4,#
Type SCK f/b -20X3	0.3	0.3	100	1(60),4,#
-1R53	3	3	330	1(113),4,#
-034	4	4	560	1(147),4,#
-035	5	5	560	1(164),4,#
-042	2	2	100	1(115),4,#
-044	4	4	560	1(159),4,#
-4R72	2	2	100	1(121),4,#
-063	3	3	100	1(145),4,#
-6R83	3	3	330	1(153),4,#
-123	3	3	470	1(158),4,#
-132	2	2	330	1(141),4,#
-133	3	3	330	1(169),4,#
-152	2	2	100	1(149),4,#
-152X	2.5	2.5	330	1(155),4,#
-162	2	2	330	1(138),4,#
-162X	2.5	2.5	330	1(152),4,#
-201	1	1	100	1(109),4,#
-252	2	2	330	1(156),4,#
-30X	0.5	0.5	100	1(84),4,#
-302	2	2	330	1(158),4,#
-472	2	2	330	1(169),4,#
-502	2	2	330	1(168),4,#
-801	1	1	200	1(140),4,#
-1001	1	1	200	1(145),4,#
-1201	1	1	200	1(131),4,#
-2R55	5	5	680	1(161),4,#
-124	4	4	560	1(188),4,#
-153	3	3	560	1(166),4,#
-163	3	3	560	1(176),4,#
-183	3	3	560	1(176),4,#
-1R58	8	8	800	1(172),4,#
-046	6	6	800	1(187),4,#
-065	5	5	680	1(177),4,#
-085	5	5	470	1(191),4,#
-086	6	6	800	1(198),4,#
-125	5	5	680	1(197),4,#
-154	4	4	680	1(192),4,#
-303	3	3	680	1(182),4,#

-802X		2.5	2.5	470	1(195),4,#
-1202		2	2	470	1(192),4,#
-064		4	4	1000	1(162),4,#
Type SCK f/b -012	240	2	2	330	1(80),4,#
-013		3	3	330	1(103),4,#
-015		5	5	150	1(140),4,#
-016		6	6	470	1(140),4,#
-018		8	8	470	1(161),4,#
-028		8	8	470	1(182),4,#
-045		5	5	330	1(174),4,#
-051		1	1	68	1(86),4,#
-073		3	3	100	1(148),4,#
-074		4	4	330	1(173),4,#
-076		6	6	470	1(196),4,#
-081		1	1	68	1(98),4,#
-096		6	6	470	1(199),4,#
-121		1	1	68	1(99),4,#
-151		1	1	100	1(106),4,#
-222		2	2	150	1(151),4,#
-224		4	4	470	1(198),4,#
-333		3	3	470	1(181),4,#
-0R78A		8	8	470	1(150),4,#
-1R35		5	5	150	1(146),4,#
-1R37		7	7	330	1(169),4,#
-1R55		5	5	150	1(148),4,#
-2R54		4	4	150	1(141),4,#
-2R57		7	7	470	1(179),4,#
-4R74		4	4	330	1(160),4,#
-4R77		7	7	470	1(198),4,#
SCK f/b -0R710	120/240	10.0	10.0	4000/1000	1(180),4
-0R712	120/240	12.0	12.0	4000/1000	1(190),4
-0R715	120/240	15.0	15.0	4000/1000	1(200), 4
-0210	120/240	10.0	10.0	4000/1000	1(195), 4
-2R510	120/240	10.0	10.0	4000/1000	1(200), 4
-0310	120/240	10.0	10.0	4000/1000	1(200), 4
-058	120/240	8.0	8.0	4000/1000	1(200), 4
-106	120/240	6.0	6.0	4000/1000	1(200), 4
-0120	120/240	20.0	20.0	3280/820	1(200), 4
-2R512	120/240	12.0	12.0	3280/820	1(190), 4
-2R515	120/240	15.0	15.0	3280/820	1(200), 4
-0510	120/240	10.0	10.0	3280/820	1(190), 4
-0512	120/240	12.0	12.0	3280/820	1(200), 4

-0710	120/240	10.0	10.0	3280/820	1(200), 4
-108	120/240	8.0	8.0	3280/820	1(200), 4
-206	120/240	6.0	6.0	2720/680	1(200), 4
SCK20 f/b -0R7	120/240	15	15	4000/1000	1(200),4,#
-1R0	120/240	13	13	4000/1000	1(200),4,#
-1R3	120/240	11.5	11.5	4000/1000	1(200),4,#
-1R5	120/240	10.5	10.5	4000/1000	1(200),4,#
-2R0	120/240	10.0	10.0	4000/1000	1(200),4,#
-2R2	120/240	9.5	9.5	4000/1000	1(200),4,#
-2R5	120/240	9.0	9.0	4000/1000	1(200),4,#
-3R0	120/240	8.5	8.5	4000/1000	1(200),4,#
-4R0	120/240	8.0	8.0	4000/1000	1(200),4,#
-4R7	120/240	7.5	7.5	4000/1000	1(200),4,#
-5R0	120/240	7.5	7.5	4000/1000	1(200),4,#
-6R0	120/240	7.0	7.0	4000/1000	1(200),4,#
-6R8	120/240	6.5	6.5	4000/1000	1(200),4,#
-7R0	120/240	6.5	6.5	4000/1000	1(200),4,#
-8R0	120/240	6.0	6.0	4000/1000	1(200),4,#
-100	120/240	5.5	5.5	4000/1000	1(200),4,#
-120	120/240	5.0	5.0	4000/1000	1(200),4,#
-130	120/240	5.0	5.0	4000/1000	1(200),4,#
-150	120/240	4.5	4.5	4000/1000	1(200),4,#
-160	120/240	4.5	4.5	4000/1000	1(200),4,#
-180	120/240	4.0	4.0	4000/1000	1(200),4,#
-200	120/240	4.0	4.0	4000/1000	1(200),4,#
SCK22 f/b -0R5	120/240	18.0	18.0	4000/1000	1(200),4,#
-0R7	120/240	16.0	16.0	4000/1000	1(200),4,#
-1R0	120/240	14.0	14.0	4000/1000	1(200),4,#
-1R3	120/240	12.0	12.0	4000/1000	1(200),4,#
-1R5	120/240	11.5	11.5	4000/1000	1(200),4,#
-2R0	120/240	11.0	11.0	4000/1000	1(200),4,#
-2R2	120/240	10.5	10.5	4000/1000	1(200),4,#
-2R5	120/240	10.0	10.0	4000/1000	1(200),4,#
-3R0	120/240	10.0	10.0	4000/1000	1(200),4,#
-4R0	120/240	9.0	9.0	4000/1000	1(200),4,#
-4R7	120/240	8.0	8.0	4000/1000	1(200),4,#
-5R0	120/240	8.0	8.0	4000/1000	1(200),4,#
-6R0	120/240	7.5	7.5	4000/1000	1(200),4,#
-6R8	120/240	7.0	7.0	4000/1000	1(200),4,#
-7R0	120/240	7.0	7.0	4000/1000	1(200),4,#
-8R0	120/240	6.5	6.5	4000/1000	1(200),4,#
-100	120/240	6.0	6.0	4000/1000	1(200),4,#

-120	120/240	6.0	6.0	4000/1000	1(200),4,#
-130	120/240	6.0	6.0	4000/1000	1(200),4,#
-150	120/240	5.0	5.0	4000/1000	1(200),4,#
-160	120/240	5.0	5.0	4000/1000	1(200),4,#
-180	120/240	4.5	4.5	4000/1000	1(200),4,#
-200	120/240	4.5	4.5	4000/1000	1(200),4,#
SCK25 f/b -1R0	120/240	20.0	20.0	4800/1200	1(200),4,#
-1R3	120/240	19.0	19.0	4800/1200	1(200),4,#
-1R5	120/240	18.5	18.5	4800/1200	1(200),4,#
-2R0	120/240	18.0	18.0	4800/1200	1(200),4,#
-2R2	120/240	16.0	16.0	4800/1200	1(200),4,#
-2R5	120/240	15.0	15.0	4800/1200	1(200),4,#
-3R0	120/240	14.5	14.5	4800/1200	1(200),4,#
-4R0	120/240	14.0	14.0	4800/1200	1(200),4,#
-4R7	120/240	13.0	13.0	4800/1200	1(200),4,#
-5R0	120/240	12.0	12.0	4800/1200	1(200),4,#
-6R0	120/240	11.0	11.0	4800/1200	1(200),4,#
-6R8	120/240	10.5	10.5	4800/1200	1(200),4,#
-7R0	120/240	10.0	10.0	4800/1200	1(200),4,#
-8R0	120/240	9.0	9.0	4800/1200	1(200),4,#
-100	120/240	8.0	8.0	4800/1200	1(200),4,#
-120	120/240	7.5	7.5	4800/1200	1(200),4,#
-130	120/240	7.0	7.0	4800/1200	1(200),4,#
-150	120/240	6.5	6.5	4800/1200	1(200),4,#
-160	120/240	6.0	6.0	4800/1200	1(200),4,#
-180	120/240	5.5	5.5	4800/1200	1(200),4,#
-200	120/240	5.0	5.0	4800/1200	1(200),4,#
SCK30 f/b -1R0	120/240	30.0	30.0	6000/1500	1(200),4,#
-1R3	120/240	26.0	26.0	6000/1500	1(200),4,#
-1R5	120/240	25.0	25.0	6000/1500	1(200),4,#
-2R0	120/240	23.0	23.0	6000/1500	1(200),4,#
-2R2	120/240	20.0	20.0	6000/1500	1(200),4,#
-2R5	120/240	18.0	18.0	6000/1500	1(200),4,#
-3R0	120/240	17.0	17.0	6000/1500	1(200),4,#
-4R0	120/240	16.0	16.0	6000/1500	1(200),4,#
-4R7	120/240	15.0	15.0	6000/1500	1(200),4,#
-5R0	120/240	14.0	14.0	6000/1500	1(200),4,#
-6R0	120/240	13.0	13.0	6000/1500	1(200),4,#
-6R8	120/240	12.0	12.0	6000/1500	1(200),4,#
-7R0	120/240	11.5	11.5	6000/1500	1(200),4,#
-8R0	120/240	10.5	10.5	6000/1500	1(200),4,#
-100	120/240	10.0	10.0	6000/1500	1(200),4,#

-120	120/240	9.0	9.0	6000/1500	1(200),4,#
-130	120/240	8.5	8.5	6000/1500	1(200),4,#
-150	120/240	8.0	8.0	6000/1500	1(200),4,#
-160	120/240	7.5	7.5	6000/1500	1(200),4,#
-180	120/240	7.0	7.0	6000/1500	1(200),4,#
-200	120/240	6.0	6.0	6000/1500	1(200),4,#

Unique conditions of acceptability.

These devices have been subjected to 100,000 cycle Endurance test and are intended for use in safety applications.

TC Sensors:

Model No.	Voltage (V)	Tmoa (C)	Class	CA
Type TTC f/b	—	125	C4	2, 4, #
-102, -103, -103J, -152, -202,				
-222, -252, -302, -332,				
-352, -402, -472, -502,				
-602, -682, -802.				
Type TTC f/b	—	100	C4	2, 4, #
-015, -020, -025, -045,				
-047, -050, -060, -085,				
-090, -101, -104, -121,				
-123, -131, -151, -153,				
-154, -181, -201, -203,				
-204, -221, -251, -253,				
-301, -303, -351, -403,				
-471, -473, -474, -501,				
-503, -561, -681,				
-683, -701.				
Type DHT f/b	—	300	C3	4
-103, -104, -203, -204, -473,				
-502, -503, may be				
f/b F, G, H, J or K.				
Type TSM f/b	—	125	C4	4, #
1 or 2, f/b				
A or B, f/b				
three numerals (0-9),				
f/b F, G, H,				
J or K, f/b				
alpha-numeric characters.				
TCF-202	<5	100	C4	2, 4, #
TTC03-901	<5	100	C4	2, 4, #
TTC03-102	<5	100	C4	2, 4, #

TTC03-152	<5	100	C4	2, 4, #
TTC03-202	<5	100	C4	2, 4, #
TTC03-222	<5	100	C4	2, 4, #
TTC03-272	<5	100	C4	2, 4, #
TTC03-302	<5	100	C4	2, 4, #
TTC03-332	<5	100	C4	2, 4, #
TTC03-472	<5	100	C4	2, 4, #
TTC03-502	<5	100	C4	2, 4, #
TTC03-682	<5	100	C4	2, 4, #
TTC03-103	<5	125	C2	2, 4, #
TTC03-113	<5	125	C3	2, 4, #
TTC03-123	<5	125	C2	2, 4, #
TTC03-153	<5	125	C2	2, 4, #
TTC03-203	<5	125	C2	2, 4, #
TTC03-223	<5	125	C2	2, 4, #
TTC03-333	<5	125	C4	2, 4, #
TTC03-473	<5	125	C4	2, 4, #
TTC03-503	<5	125	C4	2, 4, #
TTC03-683	<5	125	C4	2, 4, #
TTC03-104	<5	125	C4	2, 4, #
TTC03-154	<5	125	C4	2, 4, #
TTC03-224	<5	125	C4	2, 4, #
TTC03-334	<5	125	C4	2, 4, #
TTC03-474	<5	125	C4	2, 4, #
Types TTF, NTS(X),	—	100	C2	4, #

where (X) may be A0, E0,

F0, G0, T5, T3, TF, TC, TD,

Ts or H0, f/b

-102, -112, -122, -132, -152,

-182, -202, -222, -242, -272,

-302, -332, -362, -392, -432,

-472, -482, -502, -512, -562,

-622, -682, -752, -822, -912,

-103, -113, -123, -133, -143,

-153, -183, -203, -223, -243,

-273, -303, -333, -363, -393,

-433, -473, -503, -513, -563,

-623, -683, -753, -823, -913,

-104, -114, -124, -134, -154,

-184, -204, -224, -244, -274,

-304, -334, -364, -394, -434,

-474, -504.

Type NTS(Y),	—	150	C2	4, #
where (Y) may be A1, F1, G1				
or H1, f/b -102,				
-112, -122, -132, -152, -182,				
-202, -222, -242, -272, -302,				
-332, -362, -392, -432, -472,				
-482, -502, -512, -562, -622,				
-682, -752, -822, -912, -103,				
-113, -123, -133, -143, -153,				
-183, -203, -223, -243, -273,				
-303, -333, -363, -393, -433,				
-473, -503, -513, -563, -623,				
-683, -753, -823, -913, -104,				
-114, -124, -134, -154, -184,				
-204, -224, -244, -274, -304,				
-334, -364, -394, -434, -474, -504.				
Type TCF f/b -102, -112,	—	100	C2	4, #
-122, -132, -152, -182, -222,				
-242, -272, -302, -332, -362,				
-392, -432, -472, -482, -502,				
-512, -562, -622, -682, -752,				
-822, -912, -103, -113, -123,				
-133, -143, -153, -183, -203,				
-223, -243, -273, -303, -333,				
-363, -393, -433, -473, -503,				
-513, -563, -623, -683, -753,				
-823, -913, -104, -114, -124,				
-134, -154, -184, -204, -224,				
-244, -274, -304, -334, -364,				
-394, -434, -474 or 504.				
Type TTS f/b	—	100	C2	4, #
-102, -112, -122, -132, -152,				
-182, -202, -222, -233, -242,				
-272, -282, -284, -302, -332,				
-362, -392, -422, -432, -472,				
-482, -502, -512, -562, -622,				
-682, -752, -822, -912, -103,				
-113, -123, -133, -143, -153,				
-183, -203, -223, -243, -273,				
-303, -333, -363, -393, -403,				
-433, -473, -503, -513, -563,				

-623, -683, -753, -823, -913,				
-104, -114, -124, -134, -154,				
-184, -204, -224, -244, -274,				
-304, -334, -364, -394, -434,				
-474, -504 or -833.				
Types NTSBH503,	—	200	C2	4, #
NTSB1503.				

TC Sensors:

Model No.	Voltage (V)	Tmoa (C)	Class	CA
PTLS2101*P4**	<5	0~65	C4	2,4
PTLS2101*P5**	<5	0~75	C4	2,4
PTLS2101*P6**	<5	0~85	C4	2,4
PTLS2101*P7**	<5	0~95	C4	2,4
PTLS2101*P8**	<5	0~105	C4	2,4
PTLS2101*P9**	<5	0~115	C4	2,4
PTLS2101*A0**	<5	0~125	C4	2,4
PTMS2101*P4**	<5	0~65	C4	2,4
PTMS2101*P5**	<5	0~75	C4	2,4
PTMS2101*P6**	<5	0~85	C4	2,4
PTMS2101*P7**	<5	*0~95	C4	2,4
PTMS2101*P8**	<5	*0~105	C4	2,4
PTMS2101*P9**	<5	*0~115	C4	2,4
PTMS2101*A0**	<5	*0~125	C4	2,4
PTLS2101*P4***02	<5	*0~70	C4	2,4
PTLS2101*P5***02	<5	*0~80	C4	2,4
PTLS2101*P6***02	<5	*0~90	C4	2,4
PTLS2101*P7***03	<5	*0~100	C4	2,4
PTLS2101*P8***03	<5	*0~110	C4	2,4
PTLS2101*P9***03	<5	*0~120	C4	2,4
PTLS2101*A0***03	<5	*0~130	C4	2,4
PTMS2101*P4***02	<5	0~70	C4	2,4
PTMS2101*P5***02	<5	0~80	C4	2,4
PTMS2101*P6***02	<5	0~90	C4	2,4
PTMS2101*P7***03	<5	0~100	C4	2,4
PTMS2101*P8***03	<5	0~110	C4	2,4
PTMS2101*P9***03	<5	0~120	C4	2,4
PTMS2101*A0***03	<5	0~130	C4	2,4
PTLS2331*P4**	<5	0~65	C4	2,4
PTLS2331*P5**	<5	0~75	C4	2,4
PTLS2331*P6**	<5	0~85	C4	2,4
PTLS2331*P7**	<5	0~95	C4	2,4

PTLS2331*P8**	<5	0~105	C4	2,4
PTLS2331*P9**	<5	0~115	C4	2,4
PTLS2331*A0**	<5	0~125	C4	2,4
PTMS2331*P4**	<5	0~65	C4	2,4
PTMS2331*P5**	<5	0~75	C4	2,4
PTMS2331*P6**	<5	0~85	C4	2,4
PTMS2331*P7**	<5	0~95	C4	2,4
PTMS2331*P8**	<5	0~105	C4	2,4
PTMS2331*P9**	<5	0~115	C4	2,4
PTMS2331*A0**	<5	0~125	C4	2,4

TC Current Limiters:

Model No.	Voltage (V)	Current (A)			Isc	Tmoa	Class	CA
		Ih	It	Imax				
PPL05750-A2B2	110/220	0.050	0.15	0.5	200	85	C1	1 (150), 2, 4, 5
PPL08390-A2B7	110/220	0.075	0.240	1.2	200	85	C1	1 (150), 2, 4, 5
PPL12270-A2B7	110/220	0.120	0.350	1.5	200	85	C1	1 (150), 2, 4, 5
PPL092R0-P824	24	0.185	0.720	2.0	200	85	C2	1(130), 2,4,5
PPL083R0-P824	24	0.145	0.570	2.0	200	85	C2	1(130), 2,4,5
PPL077R0-P824	24	0.090	0.360	2.0	200	85	C2	1(130), 2,4,5
PPL07100-P824	24	0.080	0.330	2.0	200	85	C2	1(130), 2,4,5
PPL06150-P842	42	0.060	0.230	1.5	200	85	C2	1(120), 2,4,5
PPL06220-P842	42	0.045	0.220	1.1	200	85	C2	1(120), 2,4,5
PPL06330-P842	42	0.040	0.180	0.9	200	85	C2	1(120), 2,4,5
PPL06470-P842	42	0.035	0.150	0.7	200	85	C2	1(120), 2,4,5
PPL06560-P842	42	0.030	0.140	0.7	200	85	C2	1(120), 2,4,5
PPL203R9-P8B2	110/220	0.240	0.720	7.0	200	85	C2	1(150), 2,4,5
PPL155R6-P8B2	110/220	0.180	0.540	4.5	200	85	C2	1(150), 2,4,5
PPL11100-P8B2	110/220	0.120	0.360	2.3	200	85	C2	1(150), 2,4,5
PPL09150-P8B2	110/220	0.090	0.270	1.5	200	85	C2	1(150), 2,4,5
PPL09180-P8B2	110/220	0.075	0.225	1.3	200	85	C2	1(150), 2,4,5
PPL08220-P8B2	110/220	0.065	0.195	1.2	200	85	C2	1(150), 2,4,5
PPL07360-P8B2	110/220	0.045	0.180	0.7	200	85	C2	1(150), 2,4,5
PPL05680-P8B2	110/220	0.035	0.110	0.5	200	85	C2	1(150), 2,4,5
PPL03151-P8B2	110/220	0.015	0.060	0.3	200	85	C2	1(120), 2,4,5
PPL084R7-A224	24	0.295	0.700	3.5	200	85	C2	1(150), 2,4,5
PPL103R9-A224	24	0.340	0.800	4.3	200	85	C2	1(150), 2,4,5
PPL143R3-A224	24	0.420	0.980	5.0	200	85	C2	1(150), 2,4,5
PPL152R4-A263	63	0.460	1.4	7.5	200	85	C2	1(160), 2,4,5
PPL113R6-A263	63	0.320	0.960	5.0	200	85	C2	1(160), 2,4,5
PPL095R1-A263	63	0.280	0.850	4.5	200	85	C2	1(160), 2,4,5
PPL089R1-A263	63	0.160	0.480	3.0	200	85	C2	1(160), 2,4,5
PPL05240-A263	63	0.090	0.270	1.0	200	85	C2	1(160), 2,4,5

PPL03510-A263	63	0.055	0.165	0.7	200	85	C2	1(130), 2,4,5
PPL203R6-A2B2	110/220	0.460	1.38	7.0	200	85	C2	1(200), 2,4,5
PPL156R2-A2B2	110/220	0.320	0.960	4.0	200	85	C2	1(200), 2,4,5
PPL12100-A2B2	110/220	0.230	0.650	2.3	200	85	C2	1(200), 2,4,5
PPL11110-A2B2	110/220	0.200	0.600	2.2	200	85	C2	1(200), 2,4,5
PPL09160-A2B2	110/220	0.150	0.450	1.5	200	85	C2	1(200), 2,4,5
PPL08360-A2B2	110/220	0.085	0.250	1.0	200	85	C2	1(160), 2,4,5
PPL08390-A2B2	110/220	0.075	0.249	1.0	200	85	C1	1(160), 2,4,5
PPL08510-A2B2	110/220	0.065	0.195	1.0	200	85	C2	1(160), 2,4,5
PPL08620-A2B2	110/220	0.055	0.165	1.0	200	85	C2	1(160), 2,4,5
PPL06121-A2B2	110/220	0.035	0.100	0.4	200	85	C2	1(160), 2,4,5
PPL03151-A2B2	110/220	0.030	0.090	0.3	200	85	C2	1(150), 2,4,5
PPL071R0-A412	12	0.550	1.25	2.5	200	85	C2	1(195), 2,4,5
PPL12270-A2B2	110/220	0.120	0.350	1.5	200	85	C1	1(150), 2,4,5
PPL07220-A0B5	250	0.100	0.260	0.5	200	60	C1	1(150), 2, 4
PPL07500-A0C0	300	0.060	0.350	3.0	200	60	C2	1(130), 2, 4
PPL200R3-A212	12	1.800	3.600	10.0	200	60	C2	1(190), 2, 4
PPL160R5-A212	12	1.300	2.600	8.0	200	60	C2	1(190), 2, 4
PPL140R4-A212	12	0.950	2.700	5.0	200	60	C2	1(190), 2, 4
PPL140R5-A212	12	0.870	2.450	5.0	200	60	C2	1(190), 2, 4
PPL140R9-A212	12	0.430	1.210	5.0	200	60	C2	1(190), 2, 4
PPL120R8-A212	12	0.850	1.700	5.5	200	60	C2	1(190), 2, 4
PPL101R2-A212	12	0.600	1.200	4.3	200	60	C2	1(190), 2, 4
PPL091R0-A212	12	0.410	1.120	3.0	200	60	C2	1(190), 2, 4
PPL091R4-A212	12	0.350	1.060	3.0	200	60	C2	1(190), 2, 4
PPL081R8-A212	12	0.450	0.900	3.0	200	60	C2	1(190), 2, 4
PPL054R6-A212	12	0.250	0.500	1.0	200	60	C2	1(190), 2, 4
PPL04130-A212	12	0.120	0.240	0.7	200	60	C2	1(115), 2, 4
PPL201R6-A248	48	0.870	1.750	18	200	60	C3	1(150), 2, 4
PPL202R2-A248	48	0.725	1.450	14	200	60	C3	1(150), 2, 4
PPL162R6-A248	48	0.605	1.210	12	200	60	C3	1(150), 2, 4
PPL163R8-A248	48	0.505	1.010	7.3	200	60	C3	1(150), 2, 4
PPL134R3-A248	48	0.425	0.850	6.3	200	60	C3	1(150), 2, 4
PPL126R5-A248	48	0.350	0.700	4.0	200	60	C3	1(150), 2, 4
PPL129R0-A248	48	0.285	0.570	2.9	200	60	C3	1(150), 2, 4
PPL10120-A248	48	0.230	0.460	2.2	200	60	C3	1(140), 2, 4
PPL08180-A248	48	0.195	0.390	1.6	200	60	C3	1(140), 2, 4
PPL06220-A248	48	0.155	0.310	1.3	200	60	C3	1(140), 2, 4
PPL06320-A248	48	0.130	0.260	0.95	200	60	C3	1(140), 2, 4
PPL04420-A248	48	0.105	0.210	0.75	200	60	C3	1(140), 2, 4
PPL04600-A248	48	0.090	0.180	0.6	200	60	C3	1(140), 2, 4
PPL04900-A248	48	0.070	0.140	0.46	200	60	C3	1(120), 2, 4

PPL201R7-A263	63	0.700	1.400	10	200	60	C1	1(150), 2, 4
PPL164R7-A2A1	110	0.390	0.900	2.0	200	60	C1	1(160), 2, 4
PPL126R8-A2A1	110	0.290	0.660	1.0	200	60	C1	1(160), 2, 4
PPL12100-A2A1	110	0.220	0.500	1.0	200	60	C1	1(160), 2, 4
PPL205R0-A2B2	220	0.505	1.010	3.6	200	60	C2	1(180), 2, 4
PPL207R0-A2B2	220	0.425	0.850	3.0	200	60	C2	1(180), 2, 4
PPL168R0-A2B2	220	0.350	0.700	2.5	200	60	C2	1(180), 2, 4
PPL14180-A2B2	220	0.180	0.450	1.8	200	60	C2	1(180), 2, 4
PPL12140-A2B2	220	0.230	0.460	1.7	200	60	C2	1(180), 2, 4
PPL12200-A2B2	220	0.195	0.390	1.3	200	60	C2	1(160), 2, 4
PPL10150-A2B2	220	0.140	0.280	1.5	200	60	C2	1(160), 2, 4
PPL10260-A2B2	220	0.155	0.310	1.1	200	60	C2	1(160), 2, 4
PPL08240-A2B2	220	0.100	0.300	1.1	200	60	C2	1(160), 2, 4
PPL08500-A2B2	220	0.105	0.210	0.73	200	60	C2	1(160), 2, 4
PPL08720-A2B2	220	0.090	0.180	0.6	200	60	C2	1(160), 2, 4
PPL07560-A2B2	220	0.060	0.200	0.8	200	60	C2	1(140), 2, 4
PPL07820-A2B2	220	0.060	0.160	0.5	200	60	C2	1(140), 2, 4
PPL06201-A2B2	220	0.050	0.100	0.35	200	60	C2	1(140), 2, 4
PPL06281-A2B2	220	0.045	0.090	0.29	200	60	C2	1(140), 2, 4
PPL05181-A2B2	220	0.029	0.070	0.3	200	60	C2	1(140), 2, 4
PPL04381-A2B2	220	0.035	0.070	0.25	200	60	C2	1(140), 2, 4
PPL04561-A2B2	220	0.030	0.060	0.2	200	60	C2	1(140), 2, 4
PPL04851-A2B2	220	0.025	0.050	0.16	200	60	C2	1(140), 2, 4
PPL04122-A2B2	220	0.020	0.040	0.13	200	60	C2	1(140), 2, 4
PPL04192-A2B2	220	0.015	0.030	0.11	200	60	C2	1(140), 2, 4
PPL03302-A2B2	220	0.009	0.018	0.2	200	60	C2	1(120), 2, 4
PPL16500-A2B7	270	0.160	0.320	4.0	1000	60	C2	1(150), 2, 4
PPL10390-A2B7	270	0.100	0.250	1.2	1000	60	C2	1(150), 2, 4
PPL11250-A2C8	380	0.123	0.245	2.0	1000	60	C1	1(170), 2, 4
PPL11500-A2C8	380	0.087	0.173	2.0	1000	60	C1	1(170), 2, 4
PPL11800-A2C8	380	0.069	0.137	2.0	1000	60	C1	1(170), 2, 4
PPL11121-A2C8	380	0.056	0.112	2.0	1000	60	C1	1(170), 2, 4
PPL11151-A2C8	380	0.050	0.100	2.0	1000	60	C1	1(170), 2, 4
PPL08700-A2C8	380	0.064	0.127	1.4	1000	60	C1	1(170), 2, 4
PPL08121-A2C8	380	0.049	0.097	1.4	1000	60	C1	1(170), 2, 4
PPL08151-A2C8	380	0.043	0.086	1.4	1000	60	C1	1(170), 2, 4
PPL07131-A2C8	380	0.045	0.090	1.0	1000	60	C1	1(170), 2, 4
PPL05601-A2C8	380	0.021	0.039	0.2	1000	60	C1	1(130), 2, 4
PPL11501-A2E0	500	0.028	0.055	1.4	1000	60	C1	1(150), 2, 4
PPL08501-A2E0	500	0.024	0.048	1.0	1000	60	C1	1(150), 2, 4
PPL08112-A2E0	500	0.016	0.032	1.0	1000	60	C1	1(150), 2, 4
PPL05122-A2E0	500	0.015	0.030	0.1	1000	60	C1	1(150), 2, 4

PPL05152-A2E0	500	0.012	0.024	0.1	1000	60	C1	1(150), 2, 4
PPL201R2-A363	63	1.000	1.500	10	200	60	C2	1(190), 2, 4
PPL162R2-A363	63	0.700	1.100	8.0	200	60	C2	1(190), 2, 4
PPL123R3-A363	63	0.450	0.690	5.5	200	60	C2	1(190), 2, 4
PPL104R9-A363	63	0.320	0.500	4.3	200	60	C2	1(190), 2, 4
PPL088R0-A363	63	0.250	0.380	3.0	200	60	C2	1(190), 2, 4
PPL05200-A363	63	0.150	0.240	1.0	200	60	C2	1(190), 2, 4
PPL04620-A363	63	0.085	0.130	0.7	200	60	C2	1(140), 2, 4
PPL04161-A3B2	220	0.055	0.090	0.2	200	60	C1	1(150), 2, 4
PPL200R3-A424	24	2.050	4.100	23	200	60	C2	1(200), 2, 4
PPL200R4-A424	24	1.770	3.540	20	200	60	C2	1(200), 2, 4
PPL160R5-A424	24	1.390	2.780	16	200	60	C2	1(200), 2, 4
PPL160R7-A424	24	1.170	2.340	13.5	200	60	C2	1(200), 2, 4
PPL120R9-A424	24	0.920	1.840	11	200	60	C2	1(200), 2, 4
PPL121R1-A424	24	0.830	1.660	10	200	60	C2	1(200), 2, 4
PPL101R3-A424	24	0.700	1.400	8	200	60	C2	1(200), 2, 4
PPL101R7-A424	24	0.610	1.220	7	200	60	C2	1(180), 2, 4
PPL081R9-A424	24	0.540	1.080	6	200	60	C2	1(180), 2, 4
PPL082R5-A424	24	0.470	0.940	5	200	60	C2	1(180), 2, 4
PPL073R0-A424	24	0.410	0.820	4.5	200	60	C2	1(180), 2, 4
PPL075R0-A424	24	0.320	0.640	3.5	200	60	C2	1(180), 2, 4
PPL056R0-A424	24	0.270	0.540	3.5	200	60	C2	1(180), 2, 4
PPL05130-A424	24	0.180	0.360	1.7	200	60	C2	1(150), 2, 4
PPL05250-A448	48	0.130	0.260	1.2	200	60	C2	1(150), 2, 4
PPL05500-A448	48	0.094	0.188	0.8	200	60	C2	1(150), 2, 4
PPL05241-A4A1	110	0.047	0.094	0.2	200	60	C2	1(120), 2, 4
PPL05850-A4B2	220	0.076	0.152	0.55	200	60	C2	1(160), 2, 4
PPL05121-A4B2	220	0.063	0.126	0.45	200	60	C2	1(160), 2, 4
PPL05261-A4B2	220	0.039	0.078	0.3	200	60	C2	1(160), 2, 4
PPL05501-A4B2	220	0.028	0.056	0.2	200	60	C2	1(160), 2, 4
PPL05122-A4B2	220	0.019	0.038	0.14	200	60	C2	1(160), 2, 4
PPL05192-A4B2	220	0.015	0.030	0.11	200	60	C2	1(160), 2, 4
PPL05302-A4B2	220	0.011	0.022	0.08	200	60	C2	1(140), 2, 4
PPL03181-A4B2	220	0.030	0.090	0.3	200	60	C2	1(140), 2, 4
PPL05152-A0F0	600	0.014	0.028	0.2	1000	60	C2	1(140), 2, 4
PPL05272-A0F0	600	0.010	0.021	0.1	1000	60	C2	1(140), 2, 4
KRG0300090	30	0.9	1.800	40	40	85	C1	1(110), 2, 4, 5
KRG0300110	30	1.1	2.200	40	40	85	C1	1(120), 2, 4, 5
KRG0300135	30	1.35	2.700	40	40	85	C1	1(120), 2, 4, 5
KRG0300160	30	1.6	3.200	40	40	85	C1	1(120), 2, 4, 5
KRG0300185	30	1.85	3.700	40	40	85	C1	1(120), 2, 4, 5
KRG0300250	30	2.5	5.000	40	40	85	C1	1(120), 2, 4, 5

KRG0300300	30	3.0	6.000	40	40	85	C1	1(120), 2, 4, 5
KRG0300400	30	4.0	8.000	40	40	85	C1	1(120), 2, 4, 5
KRG0300500	30	5.0	10.000	40	40	85	C1	1(120), 2, 4, 5
KRG0300600	30	6.0	12.000	40	40	85	C1	1(120), 2, 4, 5
KRG0300700	30	7.0	14.000	40	40	85	C1	1(120), 2, 4, 5
KRG0300800	30	8.0	16.000	40	40	85	C1	1(120), 2, 4, 5
KRG0300900	30	9.0	18.000	40	40	85	C1	1(120), 2, 4, 5
KRG0600010	60	0.1	0.200	40	40	85	C1	1(110), 2, 4, 5
KRG0600017	60	0.17	0.340	40	40	85	C1	1(110), 2, 4, 5
KRG0600020	60	0.2	0.400	40	40	85	C1	1(110), 2, 4, 5
KRG0600025	60	0.25	0.500	40	40	85	C1	1(110), 2, 4, 5
KRG0600030	60	0.30	0.600	40	40	85	C1	1(110), 2, 4, 5
KRG0600040	60	0.40	0.800	40	40	85	C1	1(110), 2, 4, 5
KRG0600050	60	0.50	1.000	40	40	85	C1	1(110), 2, 4, 5
KRG0600065	60	0.65	1.300	40	40	85	C1	1(110), 2, 4, 5
KRG0600075	60	0.75	1.500	40	40	85	C1	1(110), 2, 4, 5
KRG0600090	60	0.9	1.800	40	40	85	C1	1(110), 2, 4, 5
KRG0600110	60	1.1	2.200	40	40	85	C1	1(120), 2, 4, 5
KRG0600135	60	1.35	2.700	40	40	85	C1	1(120), 2, 4, 5
KRG0600160	60	1.60	3.200	40	40	85	C1	1(120), 2, 4, 5
KRG0600185	60	1.85	3.700	40	40	85	C1	1(120), 2, 4, 5
KRG0600250	60	2.5	5.000	40	40	85	C1	1(120), 2, 4, 5
KRG0600300	60	3.0	6.000	40	40	85	C1	1(120), 2, 4, 5
KRG0600375	60	3.75	7.500	40	40	85	C1	1(120), 2, 4, 5
KSM0150120	15	1.2	2.700	100	100	85	C1	1(120), 2, 4, 5
KSM0150175	15	1.75	3.800	100	100	85	C1	1(120), 2, 4, 5
KSM0240200	24	2.0	4.400	100	100	85	C1	1(120), 2, 4, 5
KSM0240350	24	3.5	6.300	100	100	85	C1	1(120), 2, 4, 5
KSM0240420	24	4.2	7.600	100	100	85	C1	1(110), 2, 4, 5
KSM0150170-LR	15	1.7	3.800	100	100	85	C1	1(110), 2, 4, 5
KSM0150220-LR	15	2.2	4.500	100	100	85	C1	1(110), 2, 4, 5
KSM0240280-LR	24	2.8	6.000	100	100	85	C1	1(110), 2, 4, 5
KSH0150190	15	1.9	3.900	100	100	85	C1	1(110), 2, 4, 5
KSH0150260	15	2.6	5.800	100	100	85	C1	1(110), 2, 4, 5
KSH0150380	15	3.8	8.300	100	100	85	C1	1(110), 2, 4, 5
KSH0200450	20	4.5	8.900	100	100	85	C1	1(110), 2, 4, 5
KSH0200550	20	5.5	10.500	100	100	85	C1	1(110), 2, 4, 5
KSH0200600	20	6.0	11.700	100	100	85	C1	1(110), 2, 4, 5
KSH0200730	20	7.3	14.100	100	100	85	C1	1(110), 2, 4, 5
KSV0160170	16	1.7	3.400	100	100	85	C1	1(110), 2, 4, 5
KSV0160170-X	16	1.7	3.400	100	100	85	C1	1(110), 2, 4, 5
KSV0160175	16	1.75	3.600	100	100	85	C1	1(110), 2, 4, 5

KSV0160175-X	16	1.75	3.600	100	100	85	C1	1(110), 2, 4, 5
KSV0160210	16	2.1	4.700	100	100	85	C1	1(110), 2, 4, 5
KRG0160300	16	3.000	5.10	100	100	85	C1	1(125), 2, 5
KRG0160400	16	4.000	6.80	100	100	85	C1	1(125), 2, 5
KRG0160500	16	5.000	8.50	100	100	85	C1	1(125), 2, 5
KRG0160600	16	6.000	10.20	100	100	85	C1	1(125), 2, 5
KRG0160700	16	7.000	11.90	100	100	85	C1	1(125), 2, 5
KRG0160800	16	8.000	13.60	100	100	85	C1	1(125), 2, 5
KRG0160900	16	9.000	15.30	100	100	85	C1	1(125), 2, 5
KRG0161000	16	10.000	17.00	100	100	85	C1	1(125), 2, 5
KRG0161100	16	11.000	18.70	100	100	85	C1	1(125), 2, 5
KRG0161200	16	12.000	20.40	100	100	85	C1	1(125), 2, 5
KRG0161300	16	13.000	22.10	100	100	85	C1	1(125), 2, 5
KRG0161400	16	14.000	23.80	100	100	85	C1	1(125), 2, 5
KRG0161500	16	15.000	25.50	100	100	85	C1	1(125), 2, 5
KSV0120170	12	1.700	4.100	100	100	85	C3	1(125), 2, 4
KSV0120175	12	1.750	4.200	100	100	85	C3	1(125), 2, 4
KSV0120230	12	2.300	5.000	100	100	85	C3	1(125), 2, 4
KSV0160200	16	2.000	4.700	100	100	85	C2	1(125), 2, 4
KSV0160240	16	2.400	5.900	100	100	85	C2	1(125), 2, 4
KSL0150070	15	0.70	1.50	100	100	85	C2	1(125), 2, 4
KSL0240100	24	1.00	2.50	100	100	85	C2	1(125), 2, 4
KSL0240180	24	1.80	3.80	100	100	85	C2	1(125), 2, 4
KSL0240190	24	1.90	4.20	100	100	85	C2	1(125), 2, 4
KSL0240260	24	2.60	5.20	100	100	85	C2	1(125), 2, 4
KSL0240300	24	3.00	6.30	100	100	85	C2	1(125), 2, 4
KSL0240310	24	3.10	6.00	100	100	85	C2	1(125), 2, 4
KSL0240340	24	3.40	6.80	100	100	85	C2	1(125), 2, 4
KSH0150310	15	3.10	6.50	100	100	85	C2	1(125), 2, 4

		Current (A)					
Model No.	Vmax (dc)	Ih(#)	IT(#)	Imax	Isc	Tmoa(C)	Class
KRT2500008-U	60	0.08	0.24	3	3	-40-85	C2
KRT2500008	60	0.08	0.24	3	3	-40-85	C2
KRT2500011-U	60	0.11	0.44	3	3	-40-85	C2
KRT2500011	60	0.11	0.40	3	3	-40-85	C2
KRT2500012-U	60	0.12	0.48	3	3	-40-85	C2
KRT2500012	60	0.12	0.48	3	3	-40-85	C2
KRT2500015-U	60	0.15	0.58	3	3	-40-85	C2
KRT2500015	60	0.15	0.58	3	3	-40-85	C2
KRT2500018-U	60	0.18	0.54	3	3	-40-85	C2
KRT2500018	60	0.18	0.58	3	3	-40-85	C2
KRT6000015	60	0.15	0.60	3	3	-40-85	C2

KRT6000016		60		0.16		0.64		3		3		-40-85		C2	
Model No.	Vmax (dc)	Current (A)			Isc	Tmoa (C)	Class	CA							
		Ih(*)	It(*)	Imax											
KMC8S030	60	0.30	0.60	10	10	-40 - +85	C2	1(125),2,4,#							
KMC8S050	60	0.60	1.00	10	10	-40 - +85	C2	1(125),2,4,#							
KMC8S075	33	0.75	1.50	40	40	-40 - +85	C2	1(125),2,4,#							
KMC8S100	33	1.10	2.20	40	40	-40 - +85	C2	1(125),2,4,#							
KMC8S125	33	1.25	2.50	40	40	-40 - +85	C2	1(125),2,4,#							
KMC8S150	33	1.50	3.00	40	40	-40 - +85	C2	1(125),2,4,#							
KMC8S185	33	1.85	3.70	40	40	-40 - +85	C2	1(125),2,4,#							
KMC8S200	16	2.00	4.00	40	40	-40 - +85	C2	1(125),2,4,#							
KMC4S005	60	0.05	0.15	10	10	-40 - +85	C2	1(125),2,4,#							
KMC4S010	60	0.10	0.25	10	10	-40 - +85	C2	1(125),2,4,#							
KMC4S020	30	0.20	0.40	10	10	-40 - +85	C2	1(125),2,4,#							
KMC4S035	20	0.35	0.70	40	40	-40 - +85	C2	1(125),2,4,#							
KMC4S050	16	0.50	1.00	40	40	-40 - +85	C2	1(125),2,4,#							
KMC4S075	8	0.75	1.50	40	40	-40 - +85	C2	1(125),2,4,#							
KMC3S005	60	0.05	0.15	10	10	-40 - +85	C2	1(125),2,4,#							
KMC3S010	60	0.10	0.25	10	10	-40 - +85	C2	1(125),2,4,#							
KMC3S020	30	0.20	0.40	10	10	-40 - +85	C2	1(125),2,4,#							
KMC3S035	16	0.35	0.75	40	40	-40 - +85	C2	1(125),2,4,#							
KMC3S050	8	0.50	1.00	40	40	-40 - +85	C2	1(125),2,4,#							
KMC3S075	6	0.75	1.50	40	40	-40 - +85	C2	1(125),2,4,#							
KMC5S014	60	0.14	0.34	10	10	-40 - 85	C2	1(125),2,4,#							
KMC5S020	30	0.20	0.40	10	10	-40 - 85	C2	1(125),2,4,#							
KMC5S035	16	0.35	0.70	40	40	-40 - 85	C2	1(125),2,4,#							
KMC5S050	16	0.5	1.00	40	40	-40 - 85	C2	1(125),2,4,#							
KMC5S075	16	0.75	1.50	40	40	-40 - 85	C2	1(125),2,4,#							
KMC5S110	6	1.10	2.20	40	40	-40 - 85	C2	1(125),2,4,#							

TC Degaussers:

Model No.	Voltage (V) Vr	Current (A)		Load Impedance (ohms)	Class	CA
		Iin	Iss			
PDA8R0-P6A4	110	12.0	20	3.5	C4	1(130), 4
PDA9R0-P6A4	110	11.0	20	3.5	C4	1(130), 4
PDA120-P6A4	110	9.0	20	3.5	C4	1(130), 4
PDA7R0-P6B7	220	9.0	17	10	C4	1(140), 4
PDA9R0-P6B7	220	9.0	17	20	C4	1(140), 4
PDA120-P6B7	220	10.0	17	14	C4	1(140), 4
PDA140-P6B7	220	10.0	15	12	C4	1(140), 4
PDA180-P6B7	220	9.0	15	12	C4	1(140), 4
PDA270-P6B7	220	7.0	15	10	C4	1(140), 4
PDB3R0-P6A4	110	10	30	11	C4	1(120), #

PDB4R5-P6A4	110	9	28	10	C4	1(120), #
PDB7R0-P6A4	110	8.5	17	9	C4	1(120), #
PDB9R0-P6A4	110	7.5	17	9	C4	1(120), #
PDB120-P6A4	110	6.5	13	9	C4	1(120), #
PDB140-P6A4	110	5.0	13	14	C4	1(120), #
PDC3R0-P6A4Z	110	10	3	5	C4	1(120), #
PDC4R5-P6A4Z	110	9	3	5	C4	1(120), #
PDC7R0-P6A4Y	110	8.5	5	9	C4	1(120), #
PDC9R0-P6A4Y	110	7.5	5	9	C4	1(120), #
PDC120-P6A4Y	110	6.5	4	9	C4	1(120), #
PDC140-P6A4Y	110	5.0	4	14	C4	1(120), #
PDB4R5-P6B7	220	8.5	18	20	C4	1(120), #
PDB7R0-P6B7	220	8.5	17	20	C4	1(110), #
PDB9R0-P6B7	220	9.0	17	20	C4	1(110), #
PDB120-P6B7	220	11.0	13	12	C4	1(110), #
PDB140-P6B7	220	10.0	13	12	C4	1(110), #
PDB180-P6B7	220	9.5	11	10	C4	1(110), #
PDB270-P6B7	220	7.0	11	10	C4	1(110), #
PDC4R5-P6B7Z	220	8.5	5	20	C4	1(120), #
PDC7R0-P6B7Z	220	8.5	5	20	C4	1(120), #
PDC9R0-P6B7Z	220	9.0	4	20	C4	1(110), #
PDC120-P6B7Z	220	11.0	4	12	C4	1(110), #
PDC140-P6B7Y	220	10.0	4	12	C4	1(110), #
PDC180-P6B7Y	220	9.5	4	10	C4	1(110), #
PDC270-P6B7Y	220	7.0	4	10	C4	1(110), #
PDD1R5-P6A4	120	25.0	30	4	C4	1(110), #
PDD4R5-P6B7	220	14.5	20	14	C4	1(110), #
PDD7R0-P6B7	220	12.5	20	14	C4	1(110), #
PDD9R0-P6B7	220	11.5	17	14	C4	1(110), #
PDD120-P6B7	220	11.0	17	12	C4	1(110), #
PDG7R0-P6A4	110	8.5	17	9	C4	1(110), #
PDG9R0-P6A4	220	7.5	17	9	C4	1(110), #
PDG9R0-P6B7	220	9.0	17	20	C4	1(110), #
PDG120-P6B7	220	11.0	13	12	C4	1(110), #
PDG140-P6B7	220	11.0	13	12	C4	1(110), #
PDA3R0-P6A4	110	16	25	5	C1	1 (100), 4
PDA5R0-P6A4	110	20	20	1	C1	1 (100), 4
PDA7R0-P6A4	110	14	20	1	C1	1 (100), 4
PDA140-P6xx	220	12	15	8	C1	1 (100), 4
PDA200-P6xx	220	9	15	8	C1	1 (100), 4
PDA250-P6xx	220	8	7	6	C1	1 (100), 4
PDB1R5-P6A4	110	19	30	5.5	C1	1(120), #1

PDB5R0-P6A4	110	20	28	1	C1	1(120), #1
PDB8R0-P6A4	110	10	17	3.5	C1	1(120), #1
PDB4R5-P6xx	220	11	17	20	C2	1(120), #1
PDB7R0-P6xx	220	16	15	10	C2	1(120), #1
PDB8R0-P6xx	220	15	15	10	C2	1(120), #1
PDB9R0-P6xx	220	14	13	10	C2	1(120), #1
PDB140-P6xx	220	12	13	8	C2	1(120), #1
PDB180-P6xx	220	10	13	6	C2	1(120), #1
PDB140-P8xx	220	12	15	8	C1	1(120), #1
PDB180-P8xx	220	10	15	8	C1	1(120), #1
PDB220-P8xx	220	9	15	5	C1	1(120), #1
PDB270-P8xx	220	8	15	5	C1	1(120), #1
PDC5R0-P6A4Z	110	14	5	3.5	C1	1(120), #1
PDC8R0-P6A4Z	110	10	5	3.5	C1	1(120), #1
PDC4R5-P6xxZ	220	11	4	20	C1	1(120), #1
PDC9R0-P6xxZ	220	14	3.5	10	C1	1(120), #1
PDC140-P6xxY	220	12	3.5	8	C1	1(93), #1
PDC180-P6xxY	220	10	3.5	6	C1	1(93), #1
PDC7R0-P6xxZ	220	16	3.5	10	C1	1(120), #1
PDC360-P6xxY	220	6	3	6	C1	1(93), #1
PDC140-P8xxZ	220	12	3.5	8	C1	1(123), #1
PDC180-P8xxZ	220	10	3.5	8	C1	1(123), #1
PDD2R5-P6A4	120	23	30	3	C3	1(100), #1
PDD3R5-P6A4	120	19	30	3	C3	1(100), #1
PDD3R5-P6xx	220	17	20	13	C1	1(120), #1
PDD4R5-P6xx	220	22	20	8	C1	1(120), #1
PDD6R0-P6xx	220	22	20	6	C1	1(120), #1
PDD7R0-P6xx	220	25	16	3.5	C1	1(120), #1
PDD9R0-P6xx	220	21	16	3.5	C1	1(120), #1
PDD140-P6xx	220	14	15	3.5	C1	1(120), #1
PDD200-P6xx	220	8	13	10	C1	1(120), #1
PDD7R0-P8xx	220	16	17	10	C2	1(120), #1
PDG7R0-P6xx	220	16	15	10	C1	1(100), #1
PDG9R0-P6xx	220	14	13	10	C1	1(100), #1
PDG180-P6xx	220	10	13	6	C1	1(100), #1
PDC140-P8A4Z	110	6	5	5	C2	1(130), #1
PDC180-P8A4Z	110	5	5	5	C2	1(130), #1
PDC220-P8A4Z	110	4	4	5	C2	1(130), #1
PDC260-P8A4Z	110	3	4	5	C2	1(130), #1
PDC220-P8xxZ	220	9	4	5	C2	1(130), #1
PDC260-P8xxZ	220	8	4	5	C2	1(130), #1
PDC300-P8xxZ	220	7	4	5	C2	1(130), #1

PDD3R0-P6A4	120	16	30	5	C3	1(100), #1
PDD2R3-P6xx	220	20	22	12	C1	1(120), #1

c = B7, B8, B9 or C0.

TC Motor starting Subassemblies:

Model No.	Voltage (V)		Current		Class	CA
	Vmax	Vr	Imax (A)	Iss(mA)		
PSA3R3-AGA604	160	120	12	33	C2	1(), 4
PSA3R9-AGA604	160	120	12	33	C2	1(), 4
PSA4R7-AGA804	180	120	12	33	C2	1(), 4
PSA5R6-AGA804	180	120	12	33	C2	1(), 4
PSA6R8-AGB004	200	120	10	32	C2	1(), 4
PSA100-AGB304	230	208	9	21	C2	1(), 4
PSA150-AGB504	250	208	8	20	C2	1(), 4
PSA220-AGC004	300	240	7	17	C2	1(), 4
PSA330-AGC604	360	277	6	16	C2	1(), 4
PSA470-AGD004	400	277	5	16	C2	1(), 4
PSA680-AGD304	430	277	4	16	C2	1(), 4
PSA4R7-AGA805	180	120	10	31	C2	1(), 4
PSA5R6-AGA805	180	120	10	31	C2	1(), 4
PSA6R8-AGB005	200	120	9	31	C2	1(), 4
PSA100-AGB205	220	120	8	30	C2	1(), 4
PSA150-AGB405	240	208	7	22	C2	1(), 4
PSA220-AGB805	280	208	6	20	C2	1(), 4
PSA330-AGC205	320	240	4	18	C2	1(), 4
PSA470-AGC505	350	277	4	18	C2	1(), 4
PSA680-AGD005	400	277	4	18	C2	1(), 4
PSA4R7-AGA606	160	120	10	26	C2	1(), 4
PSA5R6-AGA706	170	120	10	26	C2	1(), 4
PSA6R8-AGA806	180	120	9	26	C2	1(), 4
PSA100-AGB006	200	120	8	26	C2	1(), 4
PSA150-AGB306	230	208	10	25	C2	1(), 4
PSA220-AGB506	250	208	6	19	C2	1(), 4
PSA6R8-AGA607	160	120	8	24	C2	1(), 4
PSA100-AGA807	180	120	7	24	C2	1(), 4
PSA150-AGB407	240	208	6	20	C2	1(), 4
PSA220-AGB407	240	208	5	20	C2	1(), 4
PSA330-AGB507	250	208	4	18	C2	1(), 4
PSA3R3-A2A604	160	120	12	33	C2	1(), 4
PSA3R9-A2A604	160	120	12	33	C2	1(), 4
PSA4R7-A2A804	180	120	12	32	C2	1(), 4
PSA5R6-A2A804	180	120	12	32	C2	1(), 4

PSA6R8-A2B204	220	120	10	30	C2	1(), 4
PSA100-A2B404	240	208	10	19	C2	1(), 4
PSA150-A2B604	260	208	10	18	C2	1(), 4
PSA220-A2C004	300	240	9	16	C2	1(), 4
PSA330-A2C004	300	240	9	16	C2	1(), 4
PSA470-A2C004	300	240	9	16	C2	1(), 4
PSA680-A2C204	320	240	9	16	C2	1(), 4
PSA4R7-A2A705	170	120	12	30	C2	1(), 4
PSA5R6-A2A905	190	120	12	30	C2	1(), 4
PSA6R8-A2B205	220	120	10	30	C2	1(), 4
PSA100-A2B405	240	208	9	18	C2	1(), 4
PSA150-A2B605	260	208	8	16	C2	1(), 4
PSA220-A2B805	280	208	8	16	C2	1(), 4
PSA330-A2B805	280	208	7	15	C2	1(), 4
PSA470-A2C005	300	240	6	15	C2	1(), 4
PSA680-A2C005	300	240	5	15	C2	1(), 4
PSB100-A2B2	220	120	9	35	C2	1(), 4
PSB150-A2B5	250	208	8	24	C2	1(), 4
PSB220-A2C0	300	240	7	23	C2	1(), 4
PSB330-A2C5	350	277	6	22	C2	1(), 4
PSB400-A2C0	300	240	5	22	C2	1(), 4
PSB470-A2D0	400	277	5	24	C2	1(), 4
PSB101-A2E0	500	277	4	30	C2	1(), 4
PSB150-A3B5	250	208	8	25	C2	1(), 4
PSB220-A3C0	300	240	7	24	C2	1(), 4
PSB330-A3C5	350	277	6	23	C2	1(), 4
PSB470-A3B5	250	208	5	23	C2	1(), 4
PS_150_33	350	277	8	15	C2	1(160), 4
PS_220_33	360	277	9	12	C2	1(160), 4
PS_250_33	350	277	9	12	C2	1(160), 4
PS_330_33	350	277	9	10	C2	1(160), 4
PS_220_04	350	277	9	10	C2	1(160), 4
PS_470_04	400	277	9	10	C2	1(160), 4
PS_4R7_05	180	120	12	20	C2	1(180), 4
PS_200_05	320	240	8	10	C2	1(180), 4
PS_220_05	320	240	8	10	C2	1(180), 4
PS_6R8_06	200	120	8	15	C2	1(180), 4
PS_100_06	200	120	8	15	C2	1(180), 4
PS_330_06	380	277	6	10	C2	1(180), 4
PS_200_07	300	240	6	20	C2	1(150), 4
PS_400_07	250	208	5	18	C2	1(150), 4
PS_470_07	250	208	5	18	C2	1(150), 4

- Unique Condition of Acceptability:

Followed by those letter M, H, N, T, P, Y and R

*Followed by alphanumeric characters

These devices are insulated with a voltage rating of 1000 + 2Vr.

Calibration Class C1 corresponds to a temperature drift of 5%.

TC heater subassemblies (pellets):

Model No.	Voltage (V)	Power (W)	Current (A)		Class	T _s (°C)	CA
			I _{in}	I _{ss}			
PHRB4302_ALA4	120	—	0.35	0.035	C2	230	1(200), 4
PHRB4123_ALB7	240	—	0.23	0.035	C2	200	1(200), 4
PHC12122_P9B7	120/240	—	0.5	0.03	C3	140	1(140), 4
PHC12122_-A1B7	120/240	—	0.6	0.04	C3	160	1(160), 4
PHC08422_A1B7	120/240	—	0.35	0.03	C3	150	1(150), 4
PHC08102_B1B7	240	—	0.5	0.04	C3	230	1(230), 4
PHC08602_B2B7	120/240	—	0.4	0.04	C3	230	1(230), 4

Marking: Company name or "E138827", or trademarks  or  , UL Recognition Mark and type designation marked on the surface of the thermistor or on the outside container.
Last Updated on 2006-06-24

[Questions?](#) [Notice of Disclaimer](#) [Page Top](#)

Copyright © 2006 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

