

Infrared Emitting Diode

Module No.: IE-0530HP


1. General Description:

IE-0530HP is a super high output power GaAlAs infrared light emitting diode, mounted in a clear epoxy end looking package. It emits narrow band of radiation peaking at 940nm.

2. Features

- Standard package (Ø5mm)
- Wide beam angle ($\pm 30^\circ$)
- Capable of pulse operation
- High output power
- Low cost

Dimensions



3. Absolute Maximum Ratings

(Ta=25°C)

Parameter	Symbol	Ratings	Unit
Forward Current	I_F	100	mA
Pulse Forward current *1	I_{FP}	1	A
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	100	mW
Operating Temperature	T_{opr}	-25 ~ +70	°C
Storage Temperature	T_{stg}	-30 ~ +80	°C
Soldering Temperature *2	T_{sol}	260	°C

*1 Pulse width $\leq 100\mu\text{sec}$. Time Cycle=10msec.


*2 At the position of 2mm from the bottom of the package within 5 seconds.

4. Electro-optical Characteristics


(Ta=25°C)

Parameter	Symbol	Testing Conditions	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F=100\text{mA}$		1.4	1.7	V
Reverse Current	I_R	$V_R=5\text{V}$			10	μA
Radiant Intensity	P_o	$I_F=100\text{mA}$	30	60		mW/sr
Terminal Capacitance	C_t	$f=1\text{MHz}$		20		pF
Half Power Beam Angle	$\Delta\theta$			± 30		deg.
Peak Emission Wavelength	λ_p	$I_F=50\text{mA}$		940		nm
Spectral bandwidth at 50%	$\Delta\lambda$	$I_F=50\text{mA}$		50		nm

Radiant Intensity vs Forward Current




Radiation Diagram




Infrared Emitting Diode

Module No.: IE-0530HP


Forward Current vs
Forward Voltage




Spectral Distribution




Power Dissipation vs
Ambient Temperature



Relative Output power vs
Ambient Temperature



Relative Power vs
Distance to Detector



Distance to Detector Test Conditions

